

Data sheet

MASTERSTOP bentonite swelling tape 25x20 mm

Dim: 25x20 mm black General Building Supervisor Board Certificate CE label





Show product



Product video in further languages





| article number: | 010011 |
|--------------------------------------------------------------------------------------|---------------------------------------------------------------|
| article group: | 100 - Masterstop 25x20 mm |
| GTIN: | 4251689510014 |
| customs tariff number: | 40027000 |
| packing unit: | cart |
| sales quantity unit: | 30 m |
| weight per: | cart = 22.8 kg |
| material: | Sodium bentonite with rubber content |
| colour: | black |
| density: | 1,54 g/m³ (DIN EN ISO 1183-1) |
| surface: | smooth |
| consistency: | malleable |
| profile: | 25x20 mm |
| weight: | 22,80 kg / carton |
| volume increase: | up to 240%, in normal water (pH 7) |
| | up to 120%, in liquids that are highly aggressive to concrete |
| | up to 220%, in alkaline liquids |
| Substances according to the SVHC list contained or proportional weight ≥0.1%:: | No |
| conform to REACH Guideline: | Yes |
| test certificate / approvals: | ETA - 16 / 0735 |
| | Investigation report, MFPA Leipzig |
| suitable for zones with frequently varying water levels: | yes |

Seite 2 von 4



| corresponds to: : | Utility class A for the wear classes 1 and |
|-------------------------|-----------------------------------------------------------|
| | 2 in accordance with the WU guideline |
| thermal scope of | approx30°C to +90°C |
| application: | |
| waterpressuretightness: | tested up to max. 8 bar (80 m watercolumn) |
| | |
| | AbP approval up to max. 2 bar (20 m watercolumn) |
| | smooth construction joints |
| | |
| | AbP approval up to max. 1,6 bar (16 m watercolumn) |
| | rough construction joints |
| storage: | Store in undamaged and unopened original packaging in a |
| | dry place out of direct sunlight. |
| disposal: | Can be disposed of at municipal waste landfill sites, |
| | taking into account the local waste disposal regulations. |
| | |



Basis

All dimensions and information in this data sheet reflect the results of the laboratory tests that have been carried out. Deviations from the values determined by us under laboratory conditions are possible due to environmental and operating conditions beyond our control. The data in this data sheet only applies for the product delivered by us. The product data corresponds only to the specifications in Germany. Possible country-specific deviations are not taken into account here.

Indication of law

The technical information reflects our current knowledge of MASTERSTOP bentonite swelling tape 25x20 mm. It is intended only as information for users. As we do not know the envisaged applications and processing conditions, it is the responsibility of the user to carefully check that the product is suitable for the intended purposes. Due to the different components at the installation site and the working conditions in place there, MASTERTEC cannot provide any guarantee whatsoever for the result of the work. Claims arising from any legal relationship can only be recognised in the event of wilful intent or gross negligence, irrespective of the statements made here or advice provided verbally. In this case the user must prove that he has provided MASTERTEC in writing with all the information required to correctly assess the installation situation in good time. Subject to necessary product specifications or further developments. By providing this information MASTERTEC does not intend to infringe third party rights. The latest data sheet in each case applies. Our corresponding terms and conditions of sale and delivery apply.

The previous data sheets are no longer valid

Print date 20.05.2024, last modified 18.11.2022