

Data sheet

MASTERSTOP SK 20x5 mm



Show product



Product video in further languages







Seite 1 von 4



article group: 101 - Masterstop SK GTIN: 4251689510175 customs tariff number: 40027000 packing unit: cart sales quantity unit: 90 m weight per: cart = 16.2 kg material: sodium bentonite colour: yellow density: 1,52 g/cm³ (DIN EN ISO 1183-1) surface: smooth consistency: malleable profile: 20 x 5 mm volume increase: up to 140%, in normal water (pH 7) Substances according to the SYHC list contained or proportional weight ≥0.1%:: conform to REACH Guideline: test certificate / approvals: MFPA Leipzig PB5.1/17-568-1 suitable for zones with frequently varying water levels: corresponds to: Utility class A for the wear classes 1 and 2 in accordance with the WU guideline packaging: size: 20 x 5 mm 90 m per carton 18 m rolls 36 cartons per pallet thermal scope of application: waterpressuretightness: up to max. 5 bar (50 m water column)	article number:	010025
customs tariff number: 40027000 packing unit: cart sales quantity unit: 90 m weight per: cart = 16.2 kg material: sodium bentonite colour: yellow density: 1,52 g/cm³ (DIN EN ISO 1183-1) surface: smooth consistency: malleable profile: 20 x 5 mm volume increase: up to 140%, in normal water (pH 7) Substances according to the SVHC list contained or proportional weight ≥0.1%:: conform to REACH Yes Guideline: test certificate / approvals: MFPA Leipzig	article group:	101 - Masterstop SK
packing unit: cart sales quantity unit: 90 m weight per: cart = 16.2 kg material: sodium bentonite colour: yellow density: 1,52 g/cm³ (DIN EN ISO 1183-1) surface: smooth consistency: malleable profile: 20 x 5 mm volume increase: up to 140%, in normal water (pH 7) Substances according to the SVHC list contained or proportional weight ≥0.1%:: conform to REACH Yes Guideline: test certificate / approvals: MFPA Leipzig PB5.1/17-568-1 suitable for zones with frequently varying water levels: corresponds to: Utility class A for the wear classes 1 and 2 in accordance with the WU guideline packaging: size: 20 x 5 mm 90 m per carton 18 m rolls 36 cartons per pallet thermal scope of approx30°C up to +90°C application:	GTIN:	4251689510175
sales quantity unit: weight per: cart = 16.2 kg material: sodium bentonite colour: yellow density: 1,52 g/cm³ (DIN EN ISO 1183-1) surface: smooth consistency: malleable profile: 20 x 5 mm volume increase: up to 140%, in normal water (pH 7) Substances according to the SVHC list contained or proportional weight ≥0.1%:: conform to REACH Guideline: test certificate / approvals: MFPA Leipzig PB5.1/17-568-1 suitable for zones with frequently varying water levels: corresponds to: Utility class A for the wear classes 1 and 2 in accordance with the WU guideline packaging: size: 20 x 5 mm 90 m per carton 18 m rolls 36 cartons per pallet thermal scope of application:	customs tariff number:	40027000
weight per: cart = 16.2 kg material: sodium bentonite colour: yellow density: 1,52 g/cm³ (DIN EN ISO 1183-1) surface: smooth consistency: malleable profile: 20 x 5 mm volume increase: up to 140%, in normal water (pH 7) Substances according to the SVHC list contained or proportional weight ≥0.1%:: No conform to REACH Guideline: Yes test certificate / approvals: MFPA Leipzig PB5.1/17-568-1 suitable for zones with frequently varying water levels: yes corresponds to: Utility class A for the wear classes 1 and 2 in accordance with the WU guideline packaging: size: 20 x 5 mm 90 m per carton 18 m rolls 36 cartons per pallet thermal scope of application: approx30°C up to +90°C	packing unit:	cart
material: sodium bentonite colour: yellow density: 1,52 g/cm³ (DIN EN ISO 1183-1) surface: smooth consistency: malleable profile: 20 x 5 mm volume increase: up to 140%, in normal water (pH 7) Substances according to the SVHC list contained or proportional weight ≥0.1%:: conform to REACH Yes Guideline: test certificate / approvals: MFPA Leipzig	sales quantity unit:	90 m
colour: yellow density: 1,52 g/cm³ (DIN EN ISO 1183-1) surface: smooth consistency: malleable profile: 20 x 5 mm volume increase: up to 140%, in normal water (pH 7) Substances according to the SVHC list contained or proportional weight ≥0.1%:: conform to REACH Yes Guideline: test certificate / approvals: MFPA Leipzig PB5.1/17-568-1 suitable for zones with frequently varying water levels: corresponds to: Utility class A for the wear classes 1 and 2 in accordance with the WU guideline packaging: size: 20 x 5 mm 90 m per carton 18 m rolls 36 cartons per pallet thermal scope of application:	weight per:	cart = 16.2 kg
density: 1,52 g/cm³ (DIN EN ISO 1183-1) surface: smooth consistency: malleable profile: 20 x 5 mm volume increase: up to 140%, in normal water (pH 7) Substances according to the SVHC list contained or proportional weight ≥0.1%:: conform to REACH Yes Guideline: test certificate / approvals: MFPA Leipzig PB5.1/17-568-1 suitable for zones with frequently varying water levels: corresponds to: Utility class A for the wear classes 1 and 2 in accordance with the WU guideline packaging: size: 20 x 5 mm 90 m per carton 18 m rolls 36 cartons per pallet thermal scope of application:	material:	sodium bentonite
surface: smooth consistency: malleable profile: 20 x 5 mm volume increase: up to 140%, in normal water (pH 7) Substances according to the SVHC list contained or proportional weight ≥0.1%:: conform to REACH Yes Guideline: test certificate / approvals: MFPA Leipzig	colour:	yellow
profile: 20 x 5 mm volume increase: up to 140%, in normal water (pH 7) Substances according to the SVHC list contained or proportional weight ≥0.1%:: conform to REACH Guideline: test certificate / approvals: MFPA Leipzig PB5.1/17-568-1 suitable for zones with yes frequently varying water levels: corresponds to: Utility class A for the wear classes 1 and 2 in accordance with the WU guideline packaging: size: 20 x 5 mm 90 m per carton 18 m rolls 36 cartons per pallet thermal scope of application:	density:	1,52 g/cm³ (DIN EN ISO 1183-1)
profile: 20 x 5 mm volume increase: up to 140%, in normal water (pH 7) Substances according to the SVHC list contained or proportional weight ≥0.1%:: conform to REACH Guideline: test certificate / approvals: mathref{PREACH} Suitable for zones with yes frequently varying water levels: corresponds to: Utility class A for the wear classes 1 and 2 in accordance with the WU guideline packaging: size: 20 x 5 mm 90 m per carton 18 m rolls 36 cartons per pallet thermal scope of approx30°C up to +90°C application:	surface:	smooth
volume increase: Substances according to the SVHC list contained or proportional weight ≥0.1%:: conform to REACH Yes Guideline: test certificate / approvals: MFPA Leipzig PB5.1/17-568-1 suitable for zones with frequently varying water levels: corresponds to: Utility class A for the wear classes 1 and 2 in accordance with the WU guideline packaging: size: 20 x 5 mm 90 m per carton 18 m rolls 36 cartons per pallet thermal scope of application:	consistency:	malleable
Substances according to the SVHC list contained or proportional weight ≥0.1%:: conform to REACH Yes Guideline: test certificate / approvals: MFPA Leipzig PB5.1/17-568-1 suitable for zones with yes frequently varying water levels: corresponds to: Utility class A for the wear classes 1 and 2 in accordance with the WU guideline packaging: size: 20 x 5 mm 90 m per carton 18 m rolls 36 cartons per pallet thermal scope of application:	profile:	20 x 5 mm
the SVHC list contained or proportional weight ≥0.1%:: conform to REACH Guideline: test certificate / approvals: MFPA Leipzig PB5.1/17-568-1 suitable for zones with frequently varying water levels: corresponds to: Utility class A for the wear classes 1 and 2 in accordance with the WU guideline packaging: size: 20 x 5 mm 90 m per carton 18 m rolls 36 cartons per pallet thermal scope of application:	volume increase:	up to 140%, in normal water (pH 7)
proportional weight ≥0.1%:: conform to REACH Guideline: test certificate / approvals: MFPA Leipzig PB5.1/17-568-1 suitable for zones with frequently varying water levels: corresponds to: Utility class A for the wear classes 1 and 2 in accordance with the WU guideline packaging: size: 20 x 5 mm 90 m per carton 18 m rolls 36 cartons per pallet thermal scope of application:	Substances according to	No
conform to REACH Guideline: test certificate / approvals: MFPA Leipzig PB5.1/17-568-1 suitable for zones with frequently varying water levels: corresponds to: Utility class A for the wear classes 1 and 2 in accordance with the WU guideline packaging: size: 20 x 5 mm 90 m per carton 18 m rolls 36 cartons per pallet thermal scope of application:	the SVHC list contained or	
Guideline: test certificate / approvals: MFPA Leipzig PB5.1/17-568-1 suitable for zones with frequently varying water levels: corresponds to: Utility class A for the wear classes 1 and 2 in accordance with the WU guideline packaging: size: 20 x 5 mm 90 m per carton 18 m rolls 36 cartons per pallet thermal scope of application:	proportional weight ≥0.1%::	
test certificate / approvals: MFPA Leipzig PB5.1/17-568-1 suitable for zones with frequently varying water levels: corresponds to: Utility class A for the wear classes 1 and 2 in accordance with the WU guideline packaging: size: 20 x 5 mm 90 m per carton 18 m rolls 36 cartons per pallet thermal scope of application:	conform to REACH	Yes
suitable for zones with frequently varying water levels: corresponds to: Utility class A for the wear classes 1 and 2 in accordance with the WU guideline packaging: size: 20 x 5 mm 90 m per carton 18 m rolls 36 cartons per pallet thermal scope of application:	Guideline:	
suitable for zones with frequently varying water levels: corresponds to: Utility class A for the wear classes 1 and 2 in accordance with the WU guideline packaging: size: 20 x 5 mm 90 m per carton 18 m rolls 36 cartons per pallet thermal scope of application:	test certificate / approvals:	. •
frequently varying water levels: corresponds to: Utility class A for the wear classes 1 and 2 in accordance with the WU guideline packaging: size: 20 x 5 mm 90 m per carton 18 m rolls 36 cartons per pallet thermal scope of approx30°C up to +90°C application:		PB5.1/17-568-1
levels: corresponds to: Utility class A for the wear classes 1 and 2 in accordance with the WU guideline packaging: size: 20 x 5 mm 90 m per carton 18 m rolls 36 cartons per pallet thermal scope of application:	suitable for zones with	yes
corresponds to: Utility class A for the wear classes 1 and 2 in accordance with the WU guideline packaging: size: 20 x 5 mm 90 m per carton 18 m rolls 36 cartons per pallet thermal scope of approx30°C up to +90°C application:		
2 in accordance with the WU guideline packaging: size: 20 x 5 mm 90 m per carton 18 m rolls 36 cartons per pallet thermal scope of approx30°C up to +90°C application:		
packaging: size: 20 x 5 mm 90 m per carton 18 m rolls 36 cartons per pallet thermal scope of approx30°C up to +90°C application:	corresponds to:	-
90 m per carton 18 m rolls 36 cartons per pallet thermal scope of approx30°C up to +90°C application:		
18 m rolls 36 cartons per pallet thermal scope of approx30°C up to +90°C application:	packaging:	
36 cartons per pallet thermal scope of approx30°C up to +90°C application:		·
thermal scope of approx30°C up to +90°C application:		
application:	The second secon	
	•	approx30°C up to +90°C
waterpressuretigntness: up to max. 5 par (50 m water column)		up to many E hay (EO many atom as larger)
	waterpressuretigntness:	up to max. 5 par (50 m water column)

Seite 2 von 4



storage:	Store in undamaged and unopened original packaging in a dry place out of direct sunlight.
disposal:	Can be disposed of at municipal waste landfill sites or waste incineration plants, taking into account the local waste disposal regulations.

Seite 3 von 4



Basis

All dimensions and information in this data sheet reflect the results of the laboratory tests that have been carried out. Deviations from the values determined by us under laboratory conditions are possible due to environmental and operating conditions beyond our control. The data in this data sheet only applies for the product delivered by us. The product data corresponds only to the specifications in Germany. Possible country-specific deviations are not taken into account here.

Indication of law

The technical information reflects our current knowledge ofMASTERSTOP SK 20x5 mm. It is intended only as information for users. As we do not know the envisaged applications and processing conditions, it is the responsibility of the user to carefully check that the product is suitable for the intended purposes. Due to the different components at the installation site and the working conditions in place there, MASTERTEC cannot provide any guarantee whatsoever for the result of the work. Claims arising from any legal relationship can only be recognised in the event of wilful intent or gross negligence, irrespective of the statements made here or advice provided verbally. In this case the user must prove that he has provided MASTERTEC in writing with all the information required to correctly assess the installation situation in good time. Subject to necessary product specifications or further developments. By providing this information MASTERTEC does not intend to infringe third party rights. The latest data sheet in each case applies. Our corresponding terms and conditions of sale and delivery apply.

The previous data sheets are no longer valid

Print date 11.05.2024, last modified 24.03.2022