

Data sheet

ABS controlled crack element 400-smooth

Type Standard; height: 310 - 400 mm





Show product



Seite 1 von 4

QUELLBÄNDER • FUGENBLECHE • INJEKTIONSSCHLÄUCHE I BAUCHEMIE • DRUCKWASSERDICHTE HAUSEINFÜHRUNGEN • BLITZSCHUTZ • SCHALUNGSZUBEHÖR

MASTERTEC GmbH & Co. KG Gewerbegebiet Unterhaid Im Maintal 13 D-96173 Oberhaid Ust.-Id.Nr.: DE 812533130 Tel.: +49 (0) 9503 5047-0 Fax: +49 (0) 9503 5047-20 info@Mastertec.eu www.Mastertec.eu EORI-Nr.: DE 4774124

Kommanditgesellschaft: HRA 9888, Sitz Oberhaid Komplementär: BBV Bau-Vertriebs-Verwaltungs GmbH, HRB 3636, Sitz Oberhaid Amtsgericht Bamberg Geschäftsführer: Rainer Kropfelder Dipl.-Kffr. Gabriele Kropfelder Felix Kropfelder Jakob Kropfelder, B.Sc.



article group:233 - ABS SollrisselementGTIN:4251689504808customs tariff number:73269098packing unit:pcsales quantity unit:2.5 mmaterial:St 37,galvanizedspecialcoating:polymer resinfabric-reinforcedcolour:crack inducing profile: silverywidth joint sheet metal:160 mmlength joint sheet metal:2.5 msuitable for zones withYesfrequently varying waterVeslevels:NoSubstances according to mroportional weight ≥0.1%:Noconform to REACH guideline:Yesthermal scope of application:-20 to +90°C	article number:	070291S
customs tariff number:73269098packing unit:pcsales quantity unit:2.5 mmaterial:St 37,galvanizedspecialcoating:polymer resinfabric-reinforcedcolour:crack inducing profile: silverycoating:blackinstallation height:310 - 400 mmwidth joint sheet metal:160 mmlength joint sheet metal:2,5 mtest certificat / approvals:MFPA Leipzigsuitable for zones with frequently varying water levels:Yessuitable for zones with frequently varying water levels:Nosuitable for zones with the SVHC list contained or proportional weight ±0.1%:Noconform to REACH guideline:Yesthermal scope of-20 to +90°C	article group:	233 - ABS Sollrisselement
packing unit:pcsales quantity unit:2.5 mmaterial:St 37,galvanizedspecialcoating:polymer resinfabric-reinforcedcolour:crack inducing profile: silverycoating: black310 - 400 mminstallation height:310 - 400 mmlength joint sheet metal:2,5 mtest certificate / approvals:MFPA Leipzigsuitable for zones with frequently varying waterYeslevels:NoSubstances according to the SVHC list contained or proportional weight ≥0.1%:Noconform to REACH guideline:Yesthermal scope of-20 to +90°C	GTIN:	4251689504808
sales quantity unit:2.5 mmaterial:St 37, galvanized special coating: polymer resin fabric- reinforcedcolour:crack inducing profile: silvery coating: blackinstallation height:310 - 400 mmwidth joint sheet metal:160 mmlength joint sheet metal:2,5 mtest certificate / approvals:MFPA Leipzigsuitable for zones with frequently varying water levels:YesSubstances according to proportional weight ≥0.1%:Noconform to REACH guideline: thermal scope of-20 to +90°C	customs tariff number:	73269098
material:St 37, galvanized special coating: polymer resin fabric- reinforcedcolour:crack inducing profile: silvery coating: blackinstallation height:310 - 400 mmwidth joint sheet metal:160 mmlength joint sheet metal:2,5 mtest certificate / approvals:MFPA Leipzigsuitable for zones with frequently varying water levels:YesSubstances according to the SVHC list contained or proportional weight ≥0.1%:Noconform to REACH guideline:Yesthermal scope of-20 to +90°C	packing unit:	рс
galvanized special coating: polymer resin fabric- reinforced colour: coating: black installation height: installation height: 310 - 400 mm coating: black installation height: 310 - 400 mm installation height:	sales quantity unit:	2.5 m
special coating: polymer resin fabric- reinforced colour: crack inducing profile: silvery coating: black installation height: 310 - 400 mm coating: black installation height: 310 - 400 mm installation height: 310 - 400 mm installation height: 310 - 400 mm installation height: 310 - 400 mm issuitable for zones with 160 mm test certificate / approvals: 75 m test ce	material:	St 37,
coating: polymer resin fabric- reinforcedcolour:crack inducing profile: silvery coating: blackinstallation height:310 - 400 mmwidth joint sheet metal:160 mmlength joint sheet metal:2,5 mtest certificate / approvals:MFPA Leipzigsuitable for zones with frequently varying water levels:Yeslevels:NoSubstances according to the SVHC list contained or proportional weight ≥0.1%:Noconform to REACH guideline:Yesthermal scope of-20 to +90°C		galvanized
polymer resin fabric- reinforcedcolour:crack inducing profile: silvery coating: blackinstallation height:310 - 400 mmwidth joint sheet metal:160 mmlength joint sheet metal:2,5 mtest certificate / approvals:MFPA Leipzigsuitable for zones with frequently varying water levels:YesSubstances according to the SVHC list contained or proportional weight ≥0.1%:Noconform to REACH guideline:Yesthermal scope of-20 to +90°C		special
fabric- reinforcedcolour:crack inducing profile: silvery coating: blackinstallation height:310 - 400 mmwidth joint sheet metal:160 mmlength joint sheet metal:2,5 mtest certificate / approvals:MFPA Leipzigsuitable for zones with frequently varying water levels:YesSubstances according to the SVHC list contained or proportional weight ≥0.1%:Noconform to REACH guideline:Yesthermal scope of-20 to +90°C		coating:
reinforcedcolour:crack inducing profile: silvery coating: blackinstallation height:310 - 400 mmwidth joint sheet metal:160 mmlength joint sheet metal:2,5 mtest certificate / approvals:MFPA Leipzigsuitable for zones with frequently varying water levels:YesSubstances according to the SVHC list contained or proportional weight ≥0.1%:Noconform to REACH guideline:Yesthermal scope of-20 to +90°C		polymer resin
colour:crack inducing profile: silvery coating: blackinstallation height:310 - 400 mmwidth joint sheet metal:160 mmlength joint sheet metal:2,5 mtest certificate / approvals:MFPA Leipzigsuitable for zones with frequently varying water levels:YesSubstances according to proportional weight ≥0.1%:Noconform to REACH guideline:Yestermal scope of-20 to +90°C		fabric-
coating: blackinstallation height:310 - 400 mmwidth joint sheet metal:160 mmlength joint sheet metal:2,5 mtest certificate / approvals:MFPA Leipzigsuitable for zones with frequently varying water levels:YesSubstances according to the SVHC list contained or proportional weight ≥0.1%:Noconform to REACH guideline:Yesthermal scope of-20 to +90°C		reinforced
installation height:310 - 400 mmwidth joint sheet metal:160 mmlength joint sheet metal:2,5 mtest certificate / approvals:MFPA Leipzigsuitable for zones with frequently varying water levels:YesSubstances according to the SVHC list contained or proportional weight ≥0.1%:Noconform to REACH guideline:Yesthermal scope of-20 to +90°C	colour:	crack inducing profile: silvery
width joint sheet metal:160 mmlength joint sheet metal:2,5 mtest certificate / approvals:MFPA Leipzigsuitable for zones with frequently varying water levels:YesSubstances according to the SVHC list contained or proportional weight ≥0.1%:Noconform to REACH guideline:Yesthermal scope of-20 to +90°C		coating: black
length joint sheet metal:2,5 mtest certificate / approvals:MFPA Leipzigsuitable for zones with frequently varying water levels:YesSubstances according to the SVHC list contained or proportional weight ≥0.1%:Noconform to REACH guideline:Yesthermal scope of-20 to +90°C	installation height:	310 - 400 mm
test certificate / approvals:MFPA Leipzigsuitable for zones with frequently varying water levels:YesSubstances according to the SVHC list contained or proportional weight ≥0.1%:Noconform to REACH guideline:Yesthermal scope of-20 to +90°C	width joint sheet metal:	160 mm
suitable for zones with frequently varying water levels:YesSubstances according to the SVHC list contained or proportional weight ≥0.1%:Noconform to REACH guideline:Yesthermal scope of-20 to +90°C	length joint sheet metal:	2,5 m
frequently varying water levels:NoSubstances according to the SVHC list contained or proportional weight ≥0.1%:Noconform to REACH guideline:Yesthermal scope of-20 to +90°C	test certificate / approvals:	MFPA Leipzig
levels:Substances according to the SVHC list contained or proportional weight ≥0.1%:Noconform to REACH guideline:Yesthermal scope of-20 to +90°C	suitable for zones with	Yes
Substances according to the SVHC list contained or proportional weight ≥0.1%:Noconform to REACH guideline:Yesthermal scope of-20 to +90°C	frequently varying water	
the SVHC list contained or proportional weight ≥0.1%:conform to REACH guideline:Yesformal scope of-20 to +90°C	levels:	
proportional weight ≥0.1%: conform to REACH Yes guideline: thermal scope of -20 to +90°C	Substances according to	No
conform to REACHYesguideline:-20 to +90°C	the SVHC list contained or	
guideline: thermal scope of -20 to +90°C	proportional weight ≥0.1%:	
thermal scope of -20 to +90°C	conform to REACH	Yes
•	guideline:	
application	thermal scope of	-20 to +90°C
	application:	
waterpressuretightness: up to 6,0 bar (60m water column)	waterpressuretightness:	up to 6,0 bar (60m water column)
storage: Store in undamaged and unopened	storage:	Store in undamaged and unopened
original packaging in a dry place out of direct sunlight.		original packaging in a dry place out of direct sunlight.

Seite 2 von 4

QUELLBÄNDER • FUGENBLECHE • INJEKTIONSSCHLÄUCHE I BAUCHEMIE • DRUCKWASSERDICHTE HAUSEINFÜHRUNGEN • BLITZSCHUTZ • SCHALUNGSZUBEHÖR

MASTERTEC GmbH & Co. KG Gewerbegebiet Unterhaid Im Maintal 13 D-96173 Oberhaid Ust.-Id.Nr.: DE 812533130 Tel.: +49 (0) 9503 5047-0 Fax: +49 (0) 9503 5047-20 info@Mastertec.eu www.Mastertec.eu EORI-Nr.: DE 4774124

Kommanditgesellschaft: HRA 9888, Sitz Oberhaid Komplementär: BBV Bau-Vertriebs-Verwaltungs GmbH, HRB 3636, Sitz Oberhaid Amtsgericht Bamberg Geschäftsführer: Rainer Kropfelder Dipl.-Kffr. Gabriele Kropfelder Felix Kropfelder Jakob Kropfelder, B.Sc.



disposal:

Can be disposed of at municipal waste landfill sites, taking into account the local waste disposal regulations.

Seite 3 von 4

QUELLBÄNDER • FUGENBLECHE • INJEKTIONSSCHLÄUCHE I BAUCHEMIE • DRUCKWASSERDICHTE HAUSEINFÜHRUNGEN • BLITZSCHUTZ • SCHALUNGSZUBEHÖR

MASTERTEC GmbH & Co. KG Gewerbegebiet Unterhaid Im Maintal 13 D-96173 Oberhaid Ust.-Id.Nr.: DE 812533130 Tel.: +49 (0) 9503 5047-0 Fax: +49 (0) 9503 5047-20 info@Mastertec.eu www.Mastertec.eu EORI-Nr.: DE 4774124

Kommanditgesellschaft: HRA 9888, Sitz Oberhaid Komplementär: BBV Bau-Vertriebs-Verwaltungs GmbH, HRB 3636, Sitz Oberhaid Amtsgericht Bamberg Geschäftsführer: Rainer Kropfelder Dipl.-Kffr. Gabriele Kropfelder Felix Kropfelder Jakob Kropfelder, B.Sc.



Basis

All dimensions and information in this data sheet reflect the results of the laboratory tests that have been carried out. Deviations from the values determined by us under laboratory conditions are possible due to environmental and operating conditions beyond our control. The data in this data sheet only applies for the product delivered by us. The product data corresponds only to the specifications in Germany. Possible country-specific deviations are not taken into account here.

Indication of law

The technical information reflects our current knowledge of ABS controlled crack element 400-smooth. It is intended only as information for users. As we do not know the envisaged applications and processing conditions, it is the responsibility of the user to carefully check that the product is suitable for the intended purposes. Due to the different components at the installation site and the working conditions in place there, MASTERTEC cannot provide any guarantee whatsoever for the result of the work. Claims arising from any legal relationship can only be recognised in the event of wilful intent or gross negligence, irrespective of the statements made here or advice provided verbally. In this case the user must prove that he has provided MASTERTEC in writing with all the information required to correctly assess the installation situation in good time. Subject to necessary product specifications or further developments. By providing this information MASTERTEC does not intend to infringe third party rights. The latest data sheet in each case applies. Our corresponding terms and conditions of sale and delivery apply.

The previous data sheets are no longer valid

Print date 18.05.2024 , last modified 03.07.2023

Seite 4 von 4

QUELLBÄNDER • FUGENBLECHE • INJEKTIONSSCHLÄUCHE I BAUCHEMIE • DRUCKWASSERDICHTE HAUSEINFÜHRUNGEN • BLITZSCHUTZ • SCHALUNGSZUBEHÖR

MASTERTEC GmbH & Co. KG Gewerbegebiet Unterhaid Im Maintal 13 D-96173 Oberhaid Ust.-Id.Nr.: DE 812533130 Tel.: +49 (0) 9503 5047-0 Fax: +49 (0) 9503 5047-20 info@Mastertec.eu www.Mastertec.eu EORI-Nr.: DE 4774124 Kommanditgesellschaft: HRA 9888, Sitz Oberhaid Komplementär: BBV Bau-Vertriebs-Verwaltungs GmbH, HRB 3636, Sitz Oberhaid Amtsgericht Bamberg **Geschäftsführer:** Rainer Kropfelder Dipl.-Kffr. Gabriele Kropfelder Felix Kropfelder Jakob Kropfelder, B.Sc.