

## Data sheet

# ABS controlled crack element 900-smooth

Type Standard; height: 810 - 900 mm







### **Show product**



Seite 1 von 4



article group: 233 - ABS sollrisselement GTIN: 4251689504969  customs tariff number: 73269098  packing unit: pc sales quantity unit: 2.5 m material: St 37,	article number:	070301S
customs tariff number: 73269098  packing unit: pc  sales quantity unit: 2.5 m  material: St 37,	article group:	233 - ABS Sollrisselement
packing unit: pc sales quantity unit: 2.5 m  material: St 37,	GTIN:	4251689504969
sales quantity unit:  material:  St 37, galvanized special coating: polymer resin fabric- reinforced  colour:  crack inducing profile: silvery coating: black  installation height: 810 - 900 mm  width joint sheet metal: length joint sheet metal: length joint sheet metal: 2,5  test certificate / approvals: suitable for zones with frequently varying water levels:  Substances according to the SVHC list contained or proportional weight ≥0.1%: conform to REACH guideline: thermal scope of application: waterpressuretightness: up to 6,0 bar (60m water column) storage: Store in undamaged and unopened	customs tariff number:	73269098
material:  St 37, galvanized special coating: polymer resin fabric- reinforced  colour:  crack inducing profile: silvery coating: black  installation height: 810 - 900 mm  width joint sheet metal: length joint sheet metal: 2,5 test certificate / approvals: MFPA Leipzig suitable for zones with frequently varying water levels: Substances according to the SVHC list contained or proportional weight ≥0.1%: conform to REACH guideline: thermal scope of application: waterpressuretightness: up to 6,0 bar (60m water column) storage: Store in undamaged and unopened	packing unit:	рс
galvanized special coating: polymer resin fabric- reinforced  colour: crack inducing profile: silvery coating: black  installation height: 810 - 900 mm  width joint sheet metal: length joint sheet metal: 2,5 test certificate / approvals: MFPA Leipzig suitable for zones with frequently varying water levels: Substances according to the SVHC list contained or proportional weight ≥0.1%: conform to REACH guideline: thermal scope of application: waterpressuretightness: up to 6,0 bar (60m water column) storage: Store in undamaged and unopened	sales quantity unit:	2.5 m
special coating: polymer resin fabric- reinforced  colour: crack inducing profile: silvery coating: black  installation height: 810 - 900 mm  width joint sheet metal: 160 mm  length joint sheet metal: 2,5  test certificate / approvals: MFPA Leipzig  suitable for zones with Yes  frequently varying water levels:  Substances according to No the SVHC list contained or proportional weight ≥0.1%: conform to REACH Yes guideline: thermal scope of -20 to +90°C application: waterpressuretightness: up to 6,0 bar (60m water column) storage: Store in undamaged and unopened	material:	St 37,
coating: polymer resin fabric- reinforced  colour: crack inducing profile: silvery coating: black  installation height: 810 - 900 mm  width joint sheet metal: 160 mm  length joint sheet metal: 2,5  test certificate / approvals: MFPA Leipzig  suitable for zones with Yes  frequently varying water levels:  Substances according to No the SVHC list contained or proportional weight ≥0.1%: conform to REACH Yes guideline: thermal scope of -20 to +90°C application: waterpressuretightness: up to 6,0 bar (60m water column) storage: Store in undamaged and unopened		galvanized
polymer resin fabric- reinforced  colour: crack inducing profile: silvery coating: black  installation height: 810 - 900 mm  width joint sheet metal: 160 mm  length joint sheet metal: 2,5  test certificate / approvals: MFPA Leipzig  suitable for zones with frequently varying water levels:  Substances according to the SVHC list contained or proportional weight ≥0.1%: conform to REACH yes guideline: thermal scope of application: waterpressuretightness: up to 6,0 bar (60m water column) storage: Store in undamaged and unopened		special
fabric- reinforced  colour: crack inducing profile: silvery coating: black  installation height: 810 - 900 mm  width joint sheet metal: 160 mm  length joint sheet metal: 2,5  test certificate / approvals: MFPA Leipzig  suitable for zones with frequently varying water levels:  Substances according to the SVHC list contained or proportional weight ≥0.1%: conform to REACH Yes guideline: thermal scope of application: waterpressuretightness: up to 6,0 bar (60m water column) storage: Store in undamaged and unopened		coating:
reinforced  colour: crack inducing profile: silvery coating: black  installation height: 810 - 900 mm  width joint sheet metal: 160 mm  length joint sheet metal: 2,5  test certificate / approvals: MFPA Leipzig suitable for zones with frequently varying water levels:  Substances according to the SVHC list contained or proportional weight ≥0.1%: conform to REACH yes guideline: thermal scope of -20 to +90°C application: waterpressuretightness: up to 6,0 bar (60m water column) storage: Store in undamaged and unopened		polymer resin
colour:  crack inducing profile: silvery coating: black  installation height:  810 - 900 mm  width joint sheet metal:  length joint sheet metal:  2,5  test certificate / approvals:  MFPA Leipzig  suitable for zones with frequently varying water levels:  Substances according to the SVHC list contained or proportional weight ≥0.1%:  conform to REACH guideline:  thermal scope of application:  waterpressuretightness:  up to 6,0 bar (60m water column)  storage:  Store in undamaged and unopened		fabric-
coating: black  installation height: 810 - 900 mm  width joint sheet metal: 160 mm  length joint sheet metal: 2,5  test certificate / approvals: MFPA Leipzig  suitable for zones with frequently varying water levels:  Substances according to the SVHC list contained or proportional weight ≥0.1%:  conform to REACH Yes  guideline:  thermal scope of application:  waterpressuretightness: up to 6,0 bar (60m water column)  storage: Store in undamaged and unopened		reinforced
installation height: 810 - 900 mm  width joint sheet metal: 160 mm  length joint sheet metal: 2,5  test certificate / approvals: MFPA Leipzig  suitable for zones with Yes  frequently varying water levels:  Substances according to No the SVHC list contained or proportional weight ≥0.1%:  conform to REACH Yes guideline: thermal scope of -20 to +90°C application:  waterpressuretightness: up to 6,0 bar (60m water column) storage: Store in undamaged and unopened	colour:	crack inducing profile: silvery
width joint sheet metal: 160 mm  length joint sheet metal: 2,5  test certificate / approvals: MFPA Leipzig  suitable for zones with Yes  frequently varying water levels:  Substances according to No the SVHC list contained or proportional weight ≥0.1%:  conform to REACH Yes guideline: thermal scope of -20 to +90°C application:  waterpressuretightness: up to 6,0 bar (60m water column) storage: Store in undamaged and unopened		coating: black
length joint sheet metal:  test certificate / approvals:  MFPA Leipzig  suitable for zones with frequently varying water levels:  Substances according to the SVHC list contained or proportional weight ≥0.1%:  conform to REACH guideline:  thermal scope of application:  waterpressuretightness: up to 6,0 bar (60m water column)  storage: Store in undamaged and unopened	installation height:	810 - 900 mm
test certificate / approvals: MFPA Leipzig  suitable for zones with Yes  frequently varying water levels:  Substances according to No the SVHC list contained or proportional weight ≥0.1%:  conform to REACH Yes guideline:  thermal scope of -20 to +90°C application:  waterpressuretightness: up to 6,0 bar (60m water column)  storage: Store in undamaged and unopened	width joint sheet metal:	160 mm
suitable for zones with frequently varying water levels:  Substances according to the SVHC list contained or proportional weight ≥0.1%:  conform to REACH guideline:  thermal scope of application:  waterpressuretightness:  up to 6,0 bar (60m water column)  storage:  Store in undamaged and unopened	length joint sheet metal:	2,5
frequently varying water levels:  Substances according to the SVHC list contained or proportional weight ≥0.1%:  conform to REACH Yes guideline:  thermal scope of -20 to +90°C  application:  waterpressuretightness: up to 6,0 bar (60m water column)  storage: Store in undamaged and unopened	test certificate / approvals:	MFPA Leipzig
levels:  Substances according to No the SVHC list contained or proportional weight ≥0.1%:  conform to REACH Yes guideline:  thermal scope of -20 to +90°C application:  waterpressuretightness: up to 6,0 bar (60m water column) storage:  Store in undamaged and unopened	suitable for zones with	Yes
Substances according to the SVHC list contained or proportional weight ≥0.1%:  conform to REACH guideline: thermal scope of application:  waterpressuretightness: up to 6,0 bar (60m water column)  storage: Store in undamaged and unopened	frequently varying water	
the SVHC list contained or proportional weight ≥0.1%:  conform to REACH Yes guideline:  thermal scope of -20 to +90°C application:  waterpressuretightness: up to 6,0 bar (60m water column)  storage: Store in undamaged and unopened	levels:	
proportional weight ≥0.1%:  conform to REACH Yes guideline:  thermal scope of -20 to +90°C application:  waterpressuretightness: up to 6,0 bar (60m water column)  storage: Store in undamaged and unopened	Substances according to	No
conform to REACH  guideline:  thermal scope of -20 to +90°C  application:  waterpressuretightness: up to 6,0 bar (60m water column)  storage: Store in undamaged and unopened	the SVHC list contained or	
guideline:  thermal scope of -20 to +90°C application:  waterpressuretightness: up to 6,0 bar (60m water column)  storage: Store in undamaged and unopened	proportional weight ≥0.1%:	
thermal scope of -20 to +90°C application:  waterpressuretightness: up to 6,0 bar (60m water column)  storage: Store in undamaged and unopened	conform to REACH	Yes
application:  waterpressuretightness: up to 6,0 bar (60m water column)  storage: Store in undamaged and unopened	guideline:	
waterpressuretightness: up to 6,0 bar (60m water column) storage: Store in undamaged and unopened	thermal scope of	-20 to +90°C
storage: Store in undamaged and unopened	application:	
	waterpressuretightness:	up to 6,0 bar (60m water column)
original population in a dry place out of direct conficts	storage:	Store in undamaged and unopened
original packaging in a dry place out or direct sunlight.		original packaging in a dry place out of direct sunlight.

Seite 2 von 4



disposal:

Can be disposed of at municipal waste landfill sites, taking into account the local waste disposal regulations.

Seite 3 von 4



#### **Basis**

All dimensions and information in this data sheet reflect the results of the laboratory tests that have been carried out. Deviations from the values determined by us under laboratory conditions are possible due to environmental and operating conditions beyond our control. The data in this data sheet only applies for the product delivered by us. The product data corresponds only to the specifications in Germany. Possible country-specific deviations are not taken into account here.

#### **Indication of law**

The technical information reflects our current knowledge of ABS controlled crack element 900-smooth. It is intended only as information for users. As we do not know the envisaged applications and processing conditions, it is the responsibility of the user to carefully check that the product is suitable for the intended purposes. Due to the different components at the installation site and the working conditions in place there, MASTERTEC cannot provide any guarantee whatsoever for the result of the work. Claims arising from any legal relationship can only be recognised in the event of wilful intent or gross negligence, irrespective of the statements made here or advice provided verbally. In this case the user must prove that he has provided MASTERTEC in writing with all the information required to correctly assess the installation situation in good time. Subject to necessary product specifications or further developments. By providing this information MASTERTEC does not intend to infringe third party rights. The latest data sheet in each case applies. Our corresponding terms and conditions of sale and delivery apply.

#### The previous data sheets are no longer valid

Print date 18.05.2024, last modified 04.07.2023