

Data sheet

Active lining pipe WELLO 400/600

PE lining pipe with an active sealing



Show product





Seite 1 von 3

QUELLBÄNDER • FUGENBLECHE • INJEKTIONSSCHLÄUCHE I BAUCHEMIE • DRUCKWASSERDICHTE HAUSEINFÜHRUNGEN • BLITZSCHUTZ • SCHALUNGSZUBEHÖR

MASTERTEC GmbH & Co. KG Gewerbegebiet Unterhaid Im Maintal 13 D-96173 Oberhaid Ust.-Id.Nr.: DE 812533130 Tel.: +49 (0) 9503 5047-0 Fax: +49 (0) 9503 5047-20 info@Mastertec.eu www.Mastertec.eu EORI-Nr.: DE 4774124

Kommanditgesellschaft: HRA 9888, Sitz Oberhaid Komplementär: BBV Bau-Vertriebs-Verwaltungs GmbH, HRB 3636, Sitz Oberhaid Amtsgericht Bamberg Geschäftsführer: Rainer Kropfelder Dipl.-Kffr. Gabriele Kropfelder Felix Kropfelder Jakob Kropfelder, B.Sc. Bankverbindung: Sparkasse Bamberg IBAN: DE24 7705 0000 0810 3458 84 BIC: BYLADEM1 SKB



article group:404 - WelloGTIN:4251689519710customs tariff number:39172110packing unit:pcsales quantity unit:1 Stkweight per:pc = 5.5 kgmaterial:pipe: PE-HDswelling tape: bentonitecolour:pipe: dark grey/blackswelling tape: ochrethermal scope ofapprox30° C to +60° Capplication:2 barstorage:Store in a dry place out of direct sunlightdisposal:Can be disposed of at municipal waste landfill sites, taking into account the local waste disposal	article number:	080208
customs tariff number:39172110packing unit:pcsales quantity unit:1 Stkweight per:pc = 5.5 kgmaterial:pipe: PE-HDswelling tape: bentonitecolour:pipe: dark grey/blackswelling tape: ochrethermal scope ofapprox30° C to +60° Capplication:2 barstorage:Store in a dry place out of direct sunlightdisposal:Can be disposed of at municipal waste landfill sites,	article group:	404 - Wello
packing unit:pcsales quantity unit:1 Stkweight per:pc = 5.5 kgmaterial:pipe: PE-HDswelling tape: bentonitecolour:pipe: dark grey/blackswelling tape: ochrethermal scope ofapprox30° C to +60° Capplication:2 barstorage:Store in a dry place out of direct sunlightdisposal:Can be disposed of at municipal waste landfill sites,	GTIN:	4251689519710
sales quantity unit:1 Stkweight per:pc = 5.5 kgmaterial:pipe: PE-HDswelling tape: bentonitecolour:pipe: dark grey/blackswelling tape: ochrethermal scope ofapprox30° C to +60° Capplication:2 barstorage:Store in a dry place out of direct sunlightdisposal:Can be disposed of at municipal waste landfill sites,	customs tariff number:	39172110
weight per:pc = 5.5 kgmaterial:pipe: PE-HDswelling tape: bentonitecolour:pipe: dark grey/blackswelling tape: ochrethermal scope ofapprox30° C to +60° Capplication:2 barstorage:2 barstorage:Store in a dry place out of direct sunlightdisposal:Can be disposed of at municipal waste landfill sites,	packing unit:	рс
material:pipe: PE-HD swelling tape: bentonitecolour:pipe: dark grey/black swelling tape: ochrethermal scope of application:approx30° C to +60° Cwaterpressuretightness:2 barstorage:Store in a dry place out of direct sunlightdisposal:Can be disposed of at municipal waste landfill sites,	sales quantity unit:	1 Stk
swelling tape: bentonitecolour:pipe: dark grey/black swelling tape: ochrethermal scope of application:approx30° C to +60° Cwaterpressuretightness:2 barstorage:Store in a dry place out of direct sunlightdisposal:Can be disposed of at municipal waste landfill sites,	weight per:	pc = 5.5 kg
colour:pipe: dark grey/black swelling tape: ochrethermal scope of application:approx30° C to +60° Cwaterpressuretightness:2 barstorage:Store in a dry place out of direct sunlightdisposal:Can be disposed of at municipal waste landfill sites,	material:	pipe: PE-HD
swelling tape: ochrethermal scope of application:waterpressuretightness:2 barstorage:Store in a dry place out of direct sunlightdisposal:Can be disposed of at municipal waste landfill sites,		swelling tape: bentonite
thermal scope of application:approx30° C to +60° Cwaterpressuretightness:2 barstorage:Store in a dry place out of direct sunlightdisposal:Can be disposed of at municipal waste landfill sites,	colour:	pipe: dark grey/black
application:waterpressuretightness:2 barstorage:Store in a dry place out of direct sunlightdisposal:Can be disposed of at municipal waste landfill sites,		swelling tape: ochre
waterpressuretightness:2 barstorage:Store in a dry place out of direct sunlightdisposal:Can be disposed of at municipal waste landfill sites,	thermal scope of	approx30° C to +60° C
storage:Store in a dry place out of direct sunlightdisposal:Can be disposed of at municipal waste landfill sites,	application:	
disposal: Can be disposed of at municipal waste landfill sites,	waterpressuretightness:	2 bar
·	storage:	Store in a dry place out of direct sunlight
taking into account the local waste disposal	disposal:	Can be disposed of at municipal waste landfill sites,
		taking into account the local waste disposal
regulations.		regulations.

Seite 2 von 3

QUELLBÄNDER • FUGENBLECHE • INJEKTIONSSCHLÄUCHE I BAUCHEMIE • DRUCKWASSERDICHTE HAUSEINFÜHRUNGEN • BLITZSCHUTZ • SCHALUNGSZUBEHÖR

MASTERTEC GmbH & Co. KG Gewerbegebiet Unterhaid Im Maintal 13 D-96173 Oberhaid Ust.-Id.Nr.: DE 812533130 Tel.: +49 (0) 9503 5047-0 Fax: +49 (0) 9503 5047-20 info@Mastertec.eu www.Mastertec.eu EORI-Nr.: DE 4774124 Kommanditgesellschaft: HRA 9888, Sitz Oberhaid Komplementär: BBV Bau-Vertriebs-Verwaltungs GmbH, HRB 3636, Sitz Oberhaid Amtsgericht Bamberg

Geschäftsführer: Rainer Kropfelder Dipl.-Kffr. Gabriele Kropfelder Felix Kropfelder Jakob Kropfelder, B.Sc. Bankverbindung: Sparkasse Bamberg IBAN: DE24 7705 0000 0810 3458 84 BIC: BYLADEM1 SKB



Basis

All dimensions and information in this data sheet reflect the results of the laboratory tests that have been carried out. Deviations from the values determined by us under laboratory conditions are possible due to environmental and operating conditions beyond our control. The data in this data sheet only applies for the product delivered by us. The product data corresponds only to the specifications in Germany. Possible country-specific deviations are not taken into account here.

Indication of law

The technical information reflects our current knowledge of Active lining pipe WELLO 400/600. It is intended only as information for users. As we do not know the envisaged applications and processing conditions, it is the responsibility of the user to carefully check that the product is suitable for the intended purposes. Due to the different components at the installation site and the working conditions in place there, MASTERTEC cannot provide any guarantee whatsoever for the result of the work. Claims arising from any legal relationship can only be recognised in the event of wilful intent or gross negligence, irrespective of the statements made here or advice provided verbally. In this case the user must prove that he has provided MASTERTEC in writing with all the information required to correctly assess the installation situation in good time. Subject to necessary product specifications or further developments. By providing this information MASTERTEC does not intend to infringe third party rights. The latest data sheet in each case applies. Our corresponding terms and conditions of sale and delivery apply.

The previous data sheets are no longer valid

Print date 17.05.2024 , last modified 24.03.2022

Seite 3 von 3

QUELLBÄNDER • FUGENBLECHE • INJEKTIONSSCHLÄUCHE I BAUCHEMIE • DRUCKWASSERDICHTE HAUSEINFÜHRUNGEN • BLITZSCHUTZ • SCHALUNGSZUBEHÖR

MASTERTEC GmbH & Co. KG Gewerbegebiet Unterhaid Im Maintal 13 D-96173 Oberhaid Ust.-Id.Nr.: DE 812533130 Tel.: +49 (0) 9503 5047-0 Fax: +49 (0) 9503 5047-20 info@Mastertec.eu www.Mastertec.eu EORI-Nr.: DE 4774124 Kommanditgesellschaft: HRA 9888, Sitz Oberhaid Komplementär: BBV Bau-Vertriebs-Verwaltungs GmbH, HRB 3636, Sitz Oberhaid Amtsgericht Bamberg **Geschäftsführer:** Rainer Kropfelder Dipl.-Kffr. Gabriele Kropfelder Felix Kropfelder Jakob Kropfelder, B.Sc. Bankverbindung: Sparkasse Bamberg IBAN: DE24 7705 0000 0810 3458 84 BIC: BYLADEM1 SKB