

## Data sheet

# Fibre cement lining pipe FASO 80/600











article group: 405 - Faso  GTIN: 4251689519987  customs tariff number: 68109900  packing unit: pc  sales quantity unit: 1 Stk  weight per: pc = 7 kg  material: asbestos-free fibre cement  colour: cement grey  density: 1,92 kg/dm³  thermal scope of as for the surrounding concrete application:  waterpressuretightness: 5 bar  firebehavior: A1  storage: dry  disposal: Can be disposed of at building material disposal regulations.	article number:	080218
customs tariff number: 68109900  packing unit: pc  sales quantity unit: 1 Stk  weight per: pc = 7 kg  material: asbestos-free fibre cement  colour: cement grey  density: 1,92 kg/dm³  thermal scope of as for the surrounding concrete  application:  waterpressuretightness: 5 bar  firebehavior: A1  storage: dry  disposal: Can be disposed of at building material  disposal sites, taking into account the	article group:	405 - Faso
packing unit:  sales quantity unit:  1 Stk  weight per:  pc = 7 kg  material:  asbestos-free fibre cement  colour:  cement grey  density:  1,92 kg/dm³  thermal scope of  as for the surrounding concrete  application:  waterpressuretightness:  5 bar  firebehavior:  A1  storage:  dry  disposal:  Can be disposed of at building material  disposal sites, taking into account the	GTIN:	4251689519987
sales quantity unit:  1 Stk  weight per:  pc = 7 kg  material:  colour:  cement grey  density:  1,92 kg/dm³  thermal scope of  as for the surrounding concrete application:  waterpressuretightness:  firebehavior:  storage:  dry  disposal:  Can be disposed of at building material disposal sites, taking into account the	customs tariff number:	68109900
weight per: pc = 7 kg  material: asbestos-free fibre cement  colour: cement grey  density: 1,92 kg/dm³  thermal scope of as for the surrounding concrete application:  waterpressuretightness: 5 bar  firebehavior: A1  storage: dry  disposal: Can be disposed of at building material disposal sites, taking into account the	packing unit:	рс
material: asbestos-free fibre cement  colour: cement grey  density: 1,92 kg/dm³  thermal scope of as for the surrounding concrete application:  waterpressuretightness: 5 bar  firebehavior: A1  storage: dry  disposal: Can be disposed of at building material disposal sites, taking into account the	sales quantity unit:	1 Stk
colour: cement grey  density: 1,92 kg/dm³  thermal scope of as for the surrounding concrete application:  waterpressuretightness: 5 bar firebehavior: A1 storage: dry disposal: Can be disposed of at building material disposal sites, taking into account the	weight per:	pc = 7 kg
density: 1,92 kg/dm³  thermal scope of as for the surrounding concrete application:  waterpressuretightness: 5 bar firebehavior: A1 storage: dry disposal: Can be disposed of at building material disposal sites, taking into account the	material:	asbestos-free fibre cement
thermal scope of as for the surrounding concrete application:  waterpressuretightness: 5 bar firebehavior: A1 storage: dry disposal: Can be disposed of at building material disposal sites, taking into account the	colour:	cement grey
application:  waterpressuretightness: 5 bar  firebehavior: A1  storage: dry  disposal: Can be disposed of at building material disposal sites, taking into account the	density:	1,92 kg/dm³
waterpressuretightness: 5 bar  firebehavior: A1  storage: dry  disposal: Can be disposed of at building material disposal sites, taking into account the	thermal scope of	as for the surrounding concrete
firebehavior:  storage:  dry  disposal:  Can be disposed of at building material disposal sites, taking into account the	application:	
storage: dry disposal: Can be disposed of at building material disposal sites, taking into account the	waterpressuretightness:	5 bar
disposal: Can be disposed of at building material disposal sites, taking into account the	firebehavior:	A1
disposal sites, taking into account the	storage:	dry
·	disposal:	Can be disposed of at building material
local waste disposal regulations.		disposal sites, taking into account the
		local waste disposal regulations.



#### **Basis**

All dimensions and information in this data sheet reflect the results of the laboratory tests that have been carried out. Deviations from the values determined by us under laboratory conditions are possible due to environmental and operating conditions beyond our control. The data in this data sheet only applies for the product delivered by us. The product data corresponds only to the specifications in Germany. Possible country-specific deviations are not taken into account here.

#### Indication of law

The technical information reflects our current knowledge ofFibre cement lining pipe FASO 80/600. It is intended only as information for users. As we do not know the envisaged applications and processing conditions, it is the responsibility of the user to carefully check that the product is suitable for the intended purposes. Due to the different components at the installation site and the working conditions in place there, MASTERTEC cannot provide any guarantee whatsoever for the result of the work. Claims arising from any legal relationship can only be recognised in the event of wilful intent or gross negligence, irrespective of the statements made here or advice provided verbally. In this case the user must prove that he has provided MASTERTEC in writing with all the information required to correctly assess the installation situation in good time. Subject to necessary product specifications or further developments. By providing this information MASTERTEC does not intend to infringe third party rights. The latest data sheet in each case applies. Our corresponding terms and conditions of sale and delivery apply.

### The previous data sheets are no longer valid

Print date 19.05.2024, last modified 24.03.2022