

Data sheet

Fibre cement lining pipe FASO 100/400









Seite 1 von 3



article group: 405 - Faso GTIN: 4251689520068 customs tariff number: 68109900 packing unit: pc sales quantity unit: 1 Stk weight per: pc = 5.7 kg material: asbestos-free fibre cement colour: cement grey density: 1,92 kg/dm³ thermal scope of as for the surrounding concrete application: waterpressuretightness: 5 bar firebehavior: A1	article number:	080226
customs tariff number: 68109900 packing unit: pc sales quantity unit: 1 Stk weight per: pc = 5.7 kg material: asbestos-free fibre cement colour: cement grey density: 1,92 kg/dm³ thermal scope of as for the surrounding concrete application: waterpressuretightness: 5 bar firebehavior: A1	article group:	405 - Faso
packing unit: sales quantity unit: 1 Stk weight per: pc = 5.7 kg material: asbestos-free fibre cement colour: cement grey density: 1,92 kg/dm³ thermal scope of as for the surrounding concrete application: waterpressuretightness: 5 bar firebehavior: A1	GTIN:	4251689520068
sales quantity unit: 1 Stk weight per: pc = 5.7 kg material: asbestos-free fibre cement colour: cement grey density: 1,92 kg/dm³ thermal scope of as for the surrounding concrete application: waterpressuretightness: 5 bar firebehavior: A1	customs tariff number:	68109900
weight per:pc = 5.7 kgmaterial:asbestos-free fibre cementcolour:cement greydensity:1,92 kg/dm³thermal scope ofas for the surrounding concreteapplication:waterpressuretightness:firebehavior:A1	packing unit:	рс
material: asbestos-free fibre cement colour: cement grey density: 1,92 kg/dm³ thermal scope of as for the surrounding concrete application: waterpressuretightness: 5 bar firebehavior: A1	sales quantity unit:	1 Stk
colour: cement grey density: 1,92 kg/dm³ thermal scope of as for the surrounding concrete application: waterpressuretightness: 5 bar firebehavior: A1	weight per:	pc = 5.7 kg
density: 1,92 kg/dm³ thermal scope of as for the surrounding concrete application: waterpressuretightness: 5 bar firebehavior: A1	material:	asbestos-free fibre cement
thermal scope of as for the surrounding concrete application: waterpressuretightness: 5 bar firebehavior: A1	colour:	cement grey
application: waterpressuretightness: 5 bar firebehavior: A1	density:	1,92 kg/dm³
waterpressuretightness: 5 bar firebehavior: A1	thermal scope of	as for the surrounding concrete
firebehavior: A1	application:	
	waterpressuretightness:	5 bar
storage dry	firebehavior:	A1
otorage.	storage:	dry
disposal: Can be disposed of at building material	disposal:	Can be disposed of at building material
disposal sites, taking into account the		disposal sites, taking into account the
local waste disposal regulations.		local waste disposal regulations.



Basis

All dimensions and information in this data sheet reflect the results of the laboratory tests that have been carried out. Deviations from the values determined by us under laboratory conditions are possible due to environmental and operating conditions beyond our control. The data in this data sheet only applies for the product delivered by us. The product data corresponds only to the specifications in Germany. Possible country-specific deviations are not taken into account here.

Indication of law

The technical information reflects our current knowledge ofFibre cement lining pipe FASO 100/400. It is intended only as information for users. As we do not know the envisaged applications and processing conditions, it is the responsibility of the user to carefully check that the product is suitable for the intended purposes. Due to the different components at the installation site and the working conditions in place there, MASTERTEC cannot provide any guarantee whatsoever for the result of the work. Claims arising from any legal relationship can only be recognised in the event of wilful intent or gross negligence, irrespective of the statements made here or advice provided verbally. In this case the user must prove that he has provided MASTERTEC in writing with all the information required to correctly assess the installation situation in good time. Subject to necessary product specifications or further developments. By providing this information MASTERTEC does not intend to infringe third party rights. The latest data sheet in each case applies. Our corresponding terms and conditions of sale and delivery apply.

The previous data sheets are no longer valid

Print date 19.05.2024, last modified 24.03.2022