

Data sheet

Fibre cement lining pipe FASO 450/300









Seite 1 von 3



article group: 405 - Faso GTIN: 4251689520839 customs tariff number: 68109900 packing unit: pc sales quantity unit: 1 Stk weight per: pc = 26.2 kg material: asbestos-free fibre cement colour: cement grey density: 1,92 kg/dm³ thermal scope of as for the surrounding concrete	
customs tariff number: 68109900 packing unit: pc sales quantity unit: 1 Stk weight per: pc = 26.2 kg material: asbestos-free fibre cement colour: cement grey density: 1,92 kg/dm³	
packing unit: sales quantity unit: 1 Stk weight per: pc = 26.2 kg material: asbestos-free fibre cement colour: cement grey density: 1,92 kg/dm³	
sales quantity unit: 1 Stk weight per: pc = 26.2 kg material: asbestos-free fibre cement colour: cement grey density: 1,92 kg/dm³	
weight per: pc = 26.2 kg material: asbestos-free fibre cement colour: cement grey density: 1,92 kg/dm³	
material: asbestos-free fibre cement colour: cement grey density: 1,92 kg/dm³	
colour: cement grey density: 1,92 kg/dm³	
density: 1,92 kg/dm³	
thermal scope of as for the surrounding concrete	
thermal scope of us for the surrounding concrete	
application:	
waterpressuretightness: 5 bar	
firebehavior: A1	
storage: dry	
disposal: Can be disposed of at building mate	erial
disposal sites, taking into account t	he
local waste disposal regulations.	



Basis

All dimensions and information in this data sheet reflect the results of the laboratory tests that have been carried out. Deviations from the values determined by us under laboratory conditions are possible due to environmental and operating conditions beyond our control. The data in this data sheet only applies for the product delivered by us. The product data corresponds only to the specifications in Germany. Possible country-specific deviations are not taken into account here.

Indication of law

The technical information reflects our current knowledge ofFibre cement lining pipe FASO 450/300. It is intended only as information for users. As we do not know the envisaged applications and processing conditions, it is the responsibility of the user to carefully check that the product is suitable for the intended purposes. Due to the different components at the installation site and the working conditions in place there, MASTERTEC cannot provide any guarantee whatsoever for the result of the work. Claims arising from any legal relationship can only be recognised in the event of wilful intent or gross negligence, irrespective of the statements made here or advice provided verbally. In this case the user must prove that he has provided MASTERTEC in writing with all the information required to correctly assess the installation situation in good time. Subject to necessary product specifications or further developments. By providing this information MASTERTEC does not intend to infringe third party rights. The latest data sheet in each case applies. Our corresponding terms and conditions of sale and delivery apply.

The previous data sheets are no longer valid

Print date 19.05.2024, last modified 24.03.2022