

## Data sheet

# Fibre cement lining pipe FASO 500/400





### **Show product**



Seite 1 von 3



article group: 405 - Faso  GTIN: 4251689520969  customs tariff number: 68109900  packing unit: pc  sales quantity unit: 1 Stk  weight per: pc = 44.7 kg  material: asbestos-free fibre cement  colour: cement grey  density: 1,92 kg/dm³  thermal scope of as for the surrounding concrete  application:  waterpressuretightness: 5 bar  firebehavior: A1  storage: dry  disposal: Can be disposed of at building material  disposal sites, taking into account the	article number:	080316
customs tariff number:  packing unit:  pc  sales quantity unit:  1 Stk  weight per:  pc = 44.7 kg  material:  colour:  cement grey  density:  1,92 kg/dm³  thermal scope of  application:  waterpressuretightness:  firebehavior:  storage:  dry  disposal:  68109900  pc  68109900  pc  68109900  pc  44.7 kg  asbestos-free fibre cement  cement  grey  density:  1,92 kg/dm³  as for the surrounding concrete  application:  waterpressuretightness:  5 bar  firebehavior:  A1  storage:  dry  Can be disposed of at building material	article group:	405 - Faso
packing unit:  sales quantity unit:  1 Stk  weight per:  pc = 44.7 kg  material:  asbestos-free fibre cement  colour:  cement grey  density:  1,92 kg/dm³  thermal scope of  as for the surrounding concrete  application:  waterpressuretightness:  5 bar  firebehavior:  A1  storage:  dry  disposal:  Can be disposed of at building material	GTIN:	4251689520969
sales quantity unit:  material:  colour:  cement grey  density:  1,92 kg/dm³  thermal scope of  application:  waterpressuretightness:  firebehavior:  storage:  disposal:  1 Stk  pc = 44.7 kg  asbestos-free fibre cement  cement  grey  1,92 kg/dm³  as for the surrounding concrete  application:  A1  storage:  dry  Can be disposed of at building material	customs tariff number:	68109900
weight per:  material:  colour:  cement grey  density:  1,92 kg/dm³  thermal scope of  application:  waterpressuretightness:  firebehavior:  storage:  dry  disposal:  pc = 44.7 kg  asbestos-free fibre cement  cement grey  1,92 kg/dm³  as for the surrounding concrete  application:  dry  dry  disposal:  Can be disposed of at building material	packing unit:	рс
material: asbestos-free fibre cement  colour: cement grey  density: 1,92 kg/dm³ thermal scope of as for the surrounding concrete application:  waterpressuretightness: 5 bar firebehavior: A1 storage: dry disposal: Can be disposed of at building material	sales quantity unit:	1 Stk
colour: cement grey  density: 1,92 kg/dm³  thermal scope of as for the surrounding concrete application:  waterpressuretightness: 5 bar  firebehavior: A1  storage: dry disposal: Can be disposed of at building material	weight per:	pc = 44.7 kg
density: 1,92 kg/dm³  thermal scope of as for the surrounding concrete application:  waterpressuretightness: 5 bar firebehavior: A1 storage: dry disposal: Can be disposed of at building material	material:	asbestos-free fibre cement
thermal scope of as for the surrounding concrete application:  waterpressuretightness: 5 bar firebehavior: A1 storage: dry disposal: Can be disposed of at building material	colour:	cement grey
application:  waterpressuretightness: 5 bar  firebehavior: A1  storage: dry  disposal: Can be disposed of at building material	density:	1,92 kg/dm³
waterpressuretightness: 5 bar firebehavior: A1 storage: dry disposal: Can be disposed of at building material	thermal scope of	as for the surrounding concrete
firebehavior: A1 storage: dry disposal: Can be disposed of at building material	application:	
storage: dry disposal: Can be disposed of at building material	waterpressuretightness:	5 bar
disposal: Can be disposed of at building material	firebehavior:	A1
	storage:	dry
disposal sites, taking into account the	disposal:	Can be disposed of at building material
		disposal sites, taking into account the
local waste disposal regulations.		local waste disposal regulations.



#### **Basis**

All dimensions and information in this data sheet reflect the results of the laboratory tests that have been carried out. Deviations from the values determined by us under laboratory conditions are possible due to environmental and operating conditions beyond our control. The data in this data sheet only applies for the product delivered by us. The product data corresponds only to the specifications in Germany. Possible country-specific deviations are not taken into account here.

#### **Indication of law**

The technical information reflects our current knowledge ofFibre cement lining pipe FASO 500/400. It is intended only as information for users. As we do not know the envisaged applications and processing conditions, it is the responsibility of the user to carefully check that the product is suitable for the intended purposes. Due to the different components at the installation site and the working conditions in place there, MASTERTEC cannot provide any guarantee whatsoever for the result of the work. Claims arising from any legal relationship can only be recognised in the event of wilful intent or gross negligence, irrespective of the statements made here or advice provided verbally. In this case the user must prove that he has provided MASTERTEC in writing with all the information required to correctly assess the installation situation in good time. Subject to necessary product specifications or further developments. By providing this information MASTERTEC does not intend to infringe third party rights. The latest data sheet in each case applies. Our corresponding terms and conditions of sale and delivery apply.

#### The previous data sheets are no longer valid

Print date 19.05.2024, last modified 24.03.2022