

## Data sheet

# Expansion joint tape, internal, D 32

tape width 320 mm roll length 25 m

### **Show product**





Seite 1 von 3



article group: 211 - PVC Fugenband und Dichtungsrohr GTIN: 4251689513558 customs tariff number: 39162000  packing unit: Roll sales quantity unit: 25 m  weight per: Roll = 62 kg  material: PVC-P  NB (incompatibles avec le bitume)  colour: black roll length: 25 m  tape width (a): 320 mm  expansion part width (b): 110 mm  expansion part thickness (c):  outside thickness (d): 3.5 mm  shore-hardness A: 72 ± 5°, acc. to DIN 53505  elongation at break: min. ≥ 275%, acc. to DIN EN ISO 527-2  tensile strength: min. ≥ 10 N/mm², DIN EN ISO 527-2  Substances according to the SVHC list contained or proportional weight ≥0.1%: conform to REACH Guideline:  storage: Store in undamaged and unopened original packaging in a dry place out of direct sunlight. disposal: Can be disposed of at municipal waste landfill sites, taking into account the local waste disposal regulations.	article number:	080670
customs tariff number:  packing unit:  Roll  sales quantity unit:  25 m  weight per:  Roll = 62 kg  material:  PVC-P  NB (incompatibles avec le bitume)  colour:  black  roll length:  25 m  tape width (a):  expansion part width (b):  110 mm  expansion part thickness  (c):  outside thickness (d):  shore-hardness A:  72 ± 5°, acc. to DIN 53505  elongation at break:  min. ≥ 275%, acc. to  DIN EN ISO 527-2  tensile strength:  min. ≥ 10 N/mm²,  DIN EN ISO 527-2  Substances according to  the SVHC list contained or  proportional weight ≥0.1%:  conform to REACH  Guideline:  storage:  Store in undamaged and unopened  original packaging in a dry place out of direct sunlight.  disposal:  Can be disposed of at municipal waste landfill sites,  taking into account the	article group:	211 - PVC Fugenband und Dichtungsrohr
packing unit:  sales quantity unit:  25 m  weight per:  Roll = 62 kg  material:  PVC-P  NB (incompatibles avec le bitume)  colour:  black  roll length:  25 m  tape width (a):  expansion part width (b):  110 mm  expansion part thickness  (c):  outside thickness (d):  shore-hardness A:  72 ± 5°, acc. to DIN 53505  elongation at break:  min. ≥ 275%, acc. to  DIN EN ISO 527-2  tensile strength:  min. ≥ 10 N/mm²,  DIN EN ISO 527-2  Substances according to the SVHC list contained or proportional weight ≥0.1%:  conform to REACH  Guideline:  storage:  Store in undamaged and unopened original packaging in a dry place out of direct sunlight.  disposal:  Can be disposed of at municipal waste landfill sites, taking into account the	GTIN:	4251689513558
sales quantity unit:  weight per: Roll = 62 kg material: PVC-P NB (incompatibles avec le bitume)  colour: black roll length: 25 m  tape width (a): 320 mm expansion part width (b): 110 mm expansion part thickness (c): outside thickness (d): shore-hardness A: 72 ± 5°, acc. to DIN 53505 elongation at break: min. ≥ 275%, acc. to DIN EN ISO 527-2  tensile strength: min. ≥ 10 N/mm², DIN EN ISO 527-2  Substances according to the SVHC list contained or proportional weight ≥0.1%: conform to REACH Guideline: storage: Store in undamaged and unopened original packaging in a dry place out of direct sunlight. disposal: Can be disposed of at municipal waste landfill sites, taking into account the	customs tariff number:	39162000
weight per: Roll = 62 kg   material: PVC-P   NB (incompatibles avec le bitume)   colour: black   roll length: 25 m   tape width (a): 320 mm   expansion part width (b): 110 mm   expansion part thickness 5 mm   (c): outside thickness (d):   outside thickness (d): 3.5 mm   shore-hardness A: 72 ± 5°, acc. to DIN 53505   elongation at break: min. ≥ 275%, acc. to   DIN EN ISO 527-2   tensile strength: min. ≥ 10 N/mm²,   DIN EN ISO 527-2   Substances according to the SVHC list contained or proportional weight ≥0.1%: No   conform to REACH Guideline: Yes   storage: Store in undamaged and unopened original packaging in a dry place out of direct sunlight.   disposal: Can be disposed of at municipal waste landfill sites, taking into account the	packing unit:	Roll
material:  PVC-P  NB (incompatibles avec le bitume)  colour: black  roll length: 25 m  tape width (a): expansion part width (b): 110 mm  expansion part thickness (c): outside thickness (d): shore-hardness A: 72 ± 5°, acc. to DIN 53505  elongation at break: min. ≥ 275%, acc. to DIN EN ISO 527-2  tensile strength: min. ≥ 10 N/mm², DIN EN ISO 527-2  Substances according to the SVHC list contained or proportional weight ≥0.1%: conform to REACH Guideline: storage: Store in undamaged and unopened original packaging in a dry place out of direct sunlight. disposal: Can be disposed of at municipal waste landfill sites, taking into account the	sales quantity unit:	25 m
NB (incompatibles avec le bitume)  colour: black  roll length: 25 m  tape width (a): expansion part width (b): 110 mm  expansion part thickness (c): outside thickness (d): shore-hardness A: 72 ± 5°, acc. to DIN 53505  elongation at break: min. ≥ 275%, acc. to DIN EN ISO 527-2  tensile strength: min. ≥ 10 N/mm², DIN EN ISO 527-2  Substances according to the SVHC list contained or proportional weight ≥0.1%: conform to REACH Guideline: storage: Store in undamaged and unopened original packaging in a dry place out of direct sunlight. disposal: Can be disposed of at municipal waste landfill sites, taking into account the	weight per:	Roll = 62 kg
colour: black  roll length: 25 m  tape width (a): 320 mm  expansion part width (b): 110 mm  expansion part thickness 5 mm  (c):  outside thickness (d): 3.5 mm  shore-hardness A: 72 ± 5°, acc. to DIN 53505  elongation at break: min. ≥ 275%, acc. to DIN EN ISO 527-2  tensile strength: min. ≥ 10 N/mm², DIN EN ISO 527-2  Substances according to the SVHC list contained or proportional weight ≥0.1%:  conform to REACH Guideline:  storage: Store in undamaged and unopened original packaging in a dry place out of direct sunlight.  disposal: Can be disposed of at municipal waste landfill sites, taking into account the	material:	PVC-P
tape width (a):  tape width (a):  expansion part width (b):  expansion part thickness (c):  outside thickness (d):  shore-hardness A:  72 ± 5°, acc. to DIN 53505  elongation at break:  min. ≥ 275%, acc. to  DIN EN ISO 527-2  tensile strength:  min. ≥ 10 N/mm²,  DIN EN ISO 527-2  Substances according to the SVHC list contained or proportional weight ≥0.1%:  conform to REACH  Guideline:  storage:  Store in undamaged and unopened original packaging in a dry place out of direct sunlight.  disposal:  Can be disposed of at municipal waste landfill sites, taking into account the		NB (incompatibles avec le bitume)
tape width (a):  expansion part width (b):  expansion part thickness (c):  outside thickness (d):  shore-hardness A:  r2 ± 5°, acc. to DIN 53505  elongation at break:  min. ≥ 275%, acc. to  DIN EN ISO 527-2  tensile strength:  min. ≥ 10 N/mm²,  DIN EN ISO 527-2  Substances according to the SVHC list contained or proportional weight ≥0.1%:  conform to REACH  Guideline:  storage:  Store in undamaged and unopened original packaging in a dry place out of direct sunlight.  disposal:  Can be disposed of at municipal waste landfill sites, taking into account the	colour:	black
expansion part width (b):  expansion part thickness (c):  outside thickness (d):  shore-hardness A:  r2 ± 5°, acc. to DIN 53505  elongation at break:  min. ≥ 275%, acc. to  DIN EN ISO 527-2  tensile strength:  min. ≥ 10 N/mm²,  DIN EN ISO 527-2  Substances according to the SVHC list contained or proportional weight ≥0.1%:  conform to REACH Guideline:  storage:  Store in undamaged and unopened original packaging in a dry place out of direct sunlight.  disposal:  Can be disposed of at municipal waste landfill sites, taking into account the	roll length:	25 m
expansion part thickness (c):  outside thickness (d):  shore-hardness A:  fore-hardness A:  elongation at break:  min. ≥ 275%, acc. to  DIN EN ISO 527-2  tensile strength:  min. ≥ 10 N/mm²,  DIN EN ISO 527-2  Substances according to the SVHC list contained or proportional weight ≥0.1%:  conform to REACH  Guideline:  storage:  Store in undamaged and unopened original packaging in a dry place out of direct sunlight.  disposal:  Can be disposed of at municipal waste landfill sites, taking into account the	tape width (a):	320 mm
(c):  outside thickness (d):  shore-hardness A:  72 ± 5°, acc. to DIN 53505  elongation at break:  min. ≥ 275%, acc. to  DIN EN ISO 527-2  tensile strength:  min. ≥ 10 N/mm²,  DIN EN ISO 527-2  Substances according to the SVHC list contained or proportional weight ≥0.1%:  conform to REACH  Guideline:  storage:  Store in undamaged and unopened original packaging in a dry place out of direct sunlight.  disposal:  Can be disposed of at municipal waste landfill sites, taking into account the	expansion part width (b):	110 mm
outside thickness (d):  shore-hardness A:  72 ± 5°, acc. to DIN 53505  elongation at break:  min. ≥ 275%, acc. to  DIN EN ISO 527-2  tensile strength:  min. ≥ 10 N/mm²,  DIN EN ISO 527-2  Substances according to the SVHC list contained or proportional weight ≥0.1%:  conform to REACH  Guideline:  storage:  Store in undamaged and unopened original packaging in a dry place out of direct sunlight.  disposal:  Can be disposed of at municipal waste landfill sites, taking into account the	expansion part thickness	5 mm
shore-hardness A:  72 ± 5°, acc. to DIN 53505  elongation at break:  min. ≥ 275%, acc. to  DIN EN ISO 527-2  tensile strength:  min. ≥ 10 N/mm²,  DIN EN ISO 527-2  Substances according to the SVHC list contained or proportional weight ≥0.1%:  conform to REACH  Guideline:  storage:  Store in undamaged and unopened original packaging in a dry place out of direct sunlight.  disposal:  Can be disposed of at municipal waste landfill sites, taking into account the	(c):	
elongation at break:  min. ≥ 275%, acc. to  DIN EN ISO 527-2  tensile strength:  min. ≥ 10 N/mm²,  DIN EN ISO 527-2  Substances according to the SVHC list contained or proportional weight ≥0.1%:  conform to REACH Guideline:  storage:  Store in undamaged and unopened original packaging in a dry place out of direct sunlight.  disposal:  Can be disposed of at municipal waste landfill sites, taking into account the	outside thickness (d):	3.5 mm
DIN EN ISO 527-2  tensile strength: min. ≥ 10 N/mm², DIN EN ISO 527-2  Substances according to the SVHC list contained or proportional weight ≥0.1%:  conform to REACH Yes Guideline:  storage: Store in undamaged and unopened original packaging in a dry place out of direct sunlight.  disposal: Can be disposed of at municipal waste landfill sites, taking into account the	shore-hardness A:	72 ± 5°, acc. to DIN 53505
tensile strength:  min. ≥ 10 N/mm²,  DIN EN ISO 527-2  Substances according to the SVHC list contained or proportional weight ≥0.1%:  conform to REACH  Guideline:  storage:  Store in undamaged and unopened original packaging in a dry place out of direct sunlight.  disposal:  Can be disposed of at municipal waste landfill sites, taking into account the	elongation at break:	min. ≥ 275%, acc. to
DIN EN ISO 527-2  Substances according to the SVHC list contained or proportional weight ≥0.1%:  conform to REACH Yes  Guideline:  storage: Store in undamaged and unopened original packaging in a dry place out of direct sunlight.  disposal: Can be disposed of at municipal waste landfill sites, taking into account the		DIN EN ISO 527-2
Substances according to the SVHC list contained or proportional weight ≥0.1%:  conform to REACH Guideline:  storage:  Store in undamaged and unopened original packaging in a dry place out of direct sunlight.  disposal:  Can be disposed of at municipal waste landfill sites, taking into account the	tensile strength:	min. ≥ 10 N/mm²,
the SVHC list contained or proportional weight ≥0.1%:  conform to REACH  Guideline:  storage:  Store in undamaged and unopened original packaging in a dry place out of direct sunlight.  disposal:  Can be disposed of at municipal waste landfill sites, taking into account the		DIN EN ISO 527-2
proportional weight ≥0.1%:  conform to REACH Yes  Guideline:  storage: Store in undamaged and unopened original packaging in a dry place out of direct sunlight.  disposal: Can be disposed of at municipal waste landfill sites, taking into account the	Substances according to	No
conform to REACH Guideline:  storage:  Store in undamaged and unopened original packaging in a dry place out of direct sunlight.  disposal:  Can be disposed of at municipal waste landfill sites, taking into account the	the SVHC list contained or	
Store in undamaged and unopened original packaging in a dry place out of direct sunlight.  disposal:  Can be disposed of at municipal waste landfill sites, taking into account the	proportional weight ≥0.1%:	
storage: Store in undamaged and unopened original packaging in a dry place out of direct sunlight.  disposal: Can be disposed of at municipal waste landfill sites, taking into account the	conform to REACH	Yes
original packaging in a dry place out of direct sunlight.  disposal:  Can be disposed of at municipal waste landfill sites, taking into account the	Guideline:	
disposal: Can be disposed of at municipal waste landfill sites, taking into account the	storage:	Store in undamaged and unopened
taking into account the		
<u> </u>	disposal:	·
local waste disposal regulations.		9
		local waste disposal regulations.

Seite 2 von 3



#### **Basis**

All dimensions and information in this data sheet reflect the results of the laboratory tests that have been carried out. Deviations from the values determined by us under laboratory conditions are possible due to environmental and operating conditions beyond our control. The data in this data sheet only applies for the product delivered by us. The product data corresponds only to the specifications in Germany. Possible country-specific deviations are not taken into account here.

#### Indication of law

The technical information reflects our current knowledge of Expansion joint tape, internal, D 32. It is intended only as information for users. As we do not know the envisaged applications and processing conditions, it is the responsibility of the user to carefully check that the product is suitable for the intended purposes. Due to the different components at the installation site and the working conditions in place there, MASTERTEC cannot provide any guarantee whatsoever for the result of the work. Claims arising from any legal relationship can only be recognised in the event of wilful intent or gross negligence, irrespective of the statements made here or advice provided verbally. In this case the user must prove that he has provided MASTERTEC in writing with all the information required to correctly assess the installation situation in good time. Subject to necessary product specifications or further developments. By providing this information MASTERTEC does not intend to infringe third party rights. The latest data sheet in each case applies. Our corresponding terms and conditions of sale and delivery apply.

#### The previous data sheets are no longer valid

Print date 17.05.2024, last modified 24.03.2022