

# Data sheet

# **PROTECT Easy 1 K**

Single-component polymer-based concrete adhesive





# Show product



# Seite 1 von 3

QUELLBÄNDER • FUGENBLECHE • INJEKTIONSSCHLÄUCHE I BAUCHEMIE • DRUCKWASSERDICHTE HAUSEINFÜHRUNGEN • BLITZSCHUTZ • SCHALUNGSZUBEHÖR

MASTERTEC GmbH & Co. KG Gewerbegebiet Unterhaid Im Maintal 13 D-96173 Oberhaid Ust.-Id.Nr.: DE 812533130 Tel.: +49 (0) 9503 5047-0 Fax: +49 (0) 9503 5047-20 info@Mastertec.eu www.Mastertec.eu EORI-Nr.: DE 4774124 Kommanditgesellschaft: HRA 9888, Sitz Oberhaid Komplementär: BBV Bau-Vertriebs-Verwaltungs GmbH, HRB 3636, Sitz Oberhaid Amtsgericht Bamberg

Geschäftsführer: Rainer Kropfelder Dipl.-Kffr. Gabriele Kropfelder Felix Kropfelder Jakob Kropfelder, B.Sc. Bankverbindung: Sparkasse Bamberg IBAN: DE24 7705 0000 0810 3458 84 BIC: BYLADEM1 SKB



article group:308 - Betonkleber (1K + 2K)GTIN:4251689515071customs tariff number:39073000packing unit:sacsales quantity unit:1 Beutmaterial:polymercolour:greydensity:ca. 1,4 g/m³processing time:20 minutes at around 23°Cviscosity:pastyApprovals/Certificates:pressure water tightness (MFPA Leipzig)fire resistance (MFPA Leipzig)scope of delivery:800 g foil bagsubstrate properties:dry, non-lip, dust-freefree from separating substances as grease, oil, etc.durability:best before 9 months after productionthermal scope ofapprox. +5° C to +40° Capplication:Waterpressuretightness:8 barfirebehavior:EI 240EI 240	article number:	040030
customs tariff number:39073000packing unit:sacsales quantity unit:1 Beutmaterial:polymercolour:greydensity:ca. 1,4 g/m³processing time:20 minutes at around 23°Cviscosity:pastyApprovals/Certificates:pressure water tightness (MFPA Leipzig)fire resistance (MFPA Leipzig)scope of delivery:800 g foil bagsubstrate properties:dry, non-lip, dust-freefree from separating substances as grease, oil, etc.durability:best before 9 months after productionthermal scope ofapprox. +5° C to +40° Capplication:8 bar	article group:	308 - Betonkleber (1K + 2K)
packing unit:sacsales quantity unit:1 Beutmaterial:polymercolour:greydensity:ca. 1,4 g/m³processing time:20 minutes at around 23°Cviscosity:pastyApprovals/Certificates:pressure water tightness (MFPA Leipzig) fire resistance (MFPA Leipzig)scope of delivery:800 g foil bagsubstrate properties:dry, non-lip, dust-free free from separating substances as grease, oil, etc.durability:best before 9 months after productionthermal scope of application:approx. +5° C to +40° C application:waterpressuretightness:8 bar	GTIN:	4251689515071
sales quantity unit:1 Beutmaterial:polymercolour:greydensity:ca. 1,4 g/m³processing time:20 minutes at around 23°Cviscosity:pastyApprovals/Certificates:pressure water tightness (MFPA Leipzig) fire resistance (MFPA Leipzig)scope of delivery:800 g foil bagsubstrate properties:dry, non-lip, dust-free free from separating substances as grease, oil, etc.durability:best before 9 months after productionthermal scope ofapprox. +5° C to +40° C application:waterpressuretightness:8 bar	customs tariff number:	39073000
material:polymercolour:greydensity:ca. 1,4 g/m³processing time:20 minutes at around 23°Cviscosity:pastyApprovals/Certificates:pressure water tightness (MFPA Leipzig)fire resistance (MFPA Leipzig)scope of delivery:800 g foil bagsubstrate properties:dry, non-lip, dust-freefree from separating substances as grease, oil, etc.durability:best before 9 months after productionthermal scope ofapprox. +5° C to +40° Capplication:% bar	packing unit:	sac
colour:greydensity:ca. 1,4 g/m³processing time:20 minutes at around 23°Cviscosity:pastyApprovals/Certificates:pressure water tightness (MFPA Leipzig) fire resistance (MFPA Leipzig)scope of delivery:800 g foil bagsubstrate properties:dry, non-lip, dust-free free from separating substances as grease, oil, etc.durability:best before 9 months after productionthermal scope ofapprox. +5° C to +40° C application:waterpressuretightness:8 bar	sales quantity unit:	1 Beut
density:ca. 1,4 g/m³processing time:20 minutes at around 23°Cviscosity:pastyApprovals/Certificates:pressure water tightness (MFPA Leipzig) fire resistance (MFPA Leipzig)scope of delivery:800 g foil bagsubstrate properties:dry, non-lip, dust-free free from separating substances as grease, oil, etc.durability:best before 9 months after productionthermal scope ofapprox. +5° C to +40° C application:waterpressuretightness:8 bar	material:	polymer
processing time:20 minutes at around 23°Cviscosity:pastyApprovals/Certificates:pressure water tightness (MFPA Leipzig) fire resistance (MFPA Leipzig)scope of delivery:800 g foil bagsubstrate properties:dry, non-lip, dust-free free from separating substances as grease, oil, etc.durability:best before 9 months after production approx. +5° C to +40° C application:waterpressuretightness:8 bar	colour:	grey
viscosity:pastyApprovals/Certificates:pressure water tightness (MFPA Leipzig) fire resistance (MFPA Leipzig)scope of delivery:800 g foil bagsubstrate properties:dry, non-lip, dust-free free from separating substances as grease, oil, etc.durability:best before 9 months after productionthermal scope of application:approx. +5° C to +40° C application:waterpressuretightness:8 bar	density:	ca. 1,4 g/m³
Approvals/Certificates:pressure water tightness (MFPA Leipzig) fire resistance (MFPA Leipzig)scope of delivery:800 g foil bagsubstrate properties:dry, non-lip, dust-free free from separating substances as grease, oil, etc.durability:best before 9 months after productionthermal scope of application:approx. +5° C to +40° C 8 bar	processing time:	20 minutes at around 23°C
fire resistance (MFPA Leipzig)scope of delivery:800 g foil bagsubstrate properties:dry, non-lip, dust-free free from separating substances as grease, oil, etc.durability:best before 9 months after productionthermal scope of application:approx. +5° C to +40° Cwaterpressuretightness:8 bar	viscosity:	pasty
scope of delivery:800 g foil bagsubstrate properties:dry, non-lip, dust-free free from separating substances as grease, oil, etc.durability:best before 9 months after productionthermal scope of application:approx. +5° C to +40° Cwaterpressuretightness:8 bar	Approvals/Certificates:	pressure water tightness (MFPA Leipzig)
substrate properties:dry, non-lip, dust-free free from separating substances as grease, oil, etc.durability:best before 9 months after productionthermal scope of application:approx. +5° C to +40° Cwaterpressuretightness:8 bar		fire resistance (MFPA Leipzig)
free from separating substances as grease, oil, etc.durability:best before 9 months after productionthermal scope of application:approx. +5° C to +40° Cwaterpressuretightness:8 bar	scope of delivery:	800 g foil bag
durability:best before 9 months after productionthermal scope of application:approx. +5° C to +40° Cwaterpressuretightness:8 bar	substrate properties:	dry, non-lip, dust-free
thermal scope of application:approx. +5° C to +40° Cwaterpressuretightness:8 bar		free from separating substances as grease, oil, etc.
application: waterpressuretightness: 8 bar	durability:	best before 9 months after production
waterpressuretightness: 8 bar	thermal scope of	approx. +5° C to +40° C
	application:	
firebehavior: EI 240	waterpressuretightness:	8 bar
	firebehavior:	EI 240
storage: Store in undamaged and unopened original packaging in a	storage:	Store in undamaged and unopened original packaging in a
dry place out of direct sunlight.		dry place out of direct sunlight.
Frost susceptible.		Frost susceptible.
disposal: Disposal in accordance with official regulations. Cured	disposal:	Disposal in accordance with official regulations. Cured
material residues: in the domestic and commercial waste.		material residues: in the domestic and commercial waste.
Material residues that have not hardenend: Dispose of as		Material residues that have not hardenend: Dispose of as
paint waste		paint waste

#### Seite 2 von 3

QUELLBÄNDER • FUGENBLECHE • INJEKTIONSSCHLÄUCHE I BAUCHEMIE • DRUCKWASSERDICHTE HAUSEINFÜHRUNGEN • BLITZSCHUTZ • SCHALUNGSZUBEHÖR

MASTERTEC GmbH & Co. KG Gewerbegebiet Unterhaid Im Maintal 13 D-96173 Oberhaid Ust.-Id.Nr.: DE 812533130 Tel.: +49 (0) 9503 5047-0 Fax: +49 (0) 9503 5047-20 info@Mastertec.eu www.Mastertec.eu EORI-Nr.: DE 4774124 Kommanditgesellschaft: HRA 9888, Sitz Oberhaid Komplementär: BBV Bau-Vertriebs-Verwaltungs GmbH, HRB 3636, Sitz Oberhaid Amtsgericht Bamberg

Geschäftsführer: Rainer Kropfelder Dipl.-Kffr. Gabriele Kropfelder Felix Kropfelder Jakob Kropfelder, B.Sc. Bankverbindung: Sparkasse Bamberg IBAN: DE24 7705 0000 0810 3458 84 BIC: BYLADEM1 SKB



# Basis

All dimensions and information in this data sheet reflect the results of the laboratory tests that have been carried out. Deviations from the values determined by us under laboratory conditions are possible due to environmental and operating conditions beyond our control. The data in this data sheet only applies for the product delivered by us. The product data corresponds only to the specifications in Germany. Possible country-specific deviations are not taken into account here.

# **Indication of law**

The technical information reflects our current knowledge of PROTECT Easy 1 K. It is intended only as information for users. As we do not know the envisaged applications and processing conditions, it is the responsibility of the user to carefully check that the product is suitable for the intended purposes. Due to the different components at the installation site and the working conditions in place there, MASTERTEC cannot provide any guarantee whatsoever for the result of the work. Claims arising from any legal relationship can only be recognised in the event of wilful intent or gross negligence, irrespective of the statements made here or advice provided verbally. In this case the user must prove that he has provided MASTERTEC in writing with all the information required to correctly assess the installation situation in good time. Subject to necessary product specifications or further developments. By providing this information MASTERTEC does not intend to infringe third party rights. The latest data sheet in each case applies. Our corresponding terms and conditions of sale and delivery apply.

# The previous data sheets are no longer valid

Print date 23.04.2024 , last modified 13.03.2024

# Seite 3 von 3

QUELLBÄNDER • FUGENBLECHE • INJEKTIONSSCHLÄUCHE I BAUCHEMIE • DRUCKWASSERDICHTE HAUSEINFÜHRUNGEN • BLITZSCHUTZ • SCHALUNGSZUBEHÖR

MASTERTEC GmbH & Co. KG Gewerbegebiet Unterhaid Im Maintal 13 D-96173 Oberhaid Ust.-Id.Nr.: DE 812533130 Tel.: +49 (0) 9503 5047-0 Fax: +49 (0) 9503 5047-20 info@Mastertec.eu www.Mastertec.eu EORI-Nr.: DE 4774124 Kommanditgesellschaft: HRA 9888, Sitz Oberhaid Komplementär: BBV Bau-Vertriebs-Verwaltungs GmbH, HRB 3636, Sitz Oberhaid Amtsgericht Bamberg **Geschäftsführer:** Rainer Kropfelder Dipl.-Kffr. Gabriele Kropfelder Felix Kropfelder Jakob Kropfelder, B.Sc. Bankverbindung: Sparkasse Bamberg IBAN: DE24 7705 0000 0810 3458 84 BIC: BYLADEM1 SKB