

data sheet download

LIDOL 200L MULTI

concrete release agent

[Show product](#)



Seite 1 von 4

QUELLBÄNDER • FUGENBLECHE • INJEKTIONSSCHLÄUCHE | BAUCHEMIE • DRUCKWASSERDICHTHE HAUSEINFÜHRUNGEN • BLITZSCHUTZ • SCHALUNGSZUBEHÖR

MASTERTEC GmbH & Co. KG
Gewerbegebiet Unterhaid
Im Maintal 13
D-96173 Oberhaid
Ust.-Id.Nr.: DE 812533130

Tel.: +49 (0) 9503 5047-0
Fax: +49 (0) 9503 5047-20
info@Mastertec.eu
www.Mastertec.eu
EORI-Nr.: DE 4774124

Kommanditgesellschaft:
HRA 9888, Sitz Oberhaid
Komplementär: BBV Bau-
Vertriebs-Verwaltungs GmbH,
HRB 3636, Sitz Oberhaid
Amtsgericht Bamberg

Geschäftsführer:
Rainer Kropfelder
Dipl.-Kffr. Gabriele Kropfelder
Felix Kropfelder
Jakob Kropfelder, B.Sc.

Bankverbindung:
Sparkasse Bamberg
IBAN: DE24 7705 0000 0810 3458 84
BIC: BYLADEM1 SKB

article number:	040320
GTIN:	4251689515422
customs tariff number:	27101991
packing unit:	cask
sales quantity unit:	200 Liter
weight per:	cask = 192 kg
material:	Mineral oil
colour:	colorless - yellowish
consistency:	fluid
	viscosity/20 °C: 19,5 mm ² /s (ASTM D 7042)
	viscosity/40 °C: 9 mm ² /s (ASTM D 7042)
	viscosity Index: 94 (ASTM D 2270)
density:	approx. 850 kg/m ³
pourpoint / DIN ISO 3016:	< -10 °C
flash point (accord. Cleveland) / DIN ISO 2592:	130 °C
GISCODE:	BTM 20
water hazard class:	1 = low hazard to water (accord. AwSV)
application temperature:	non frost susceptible
	Thickening at 0 ° C are not reversible
VOC:	free
packaging:	200 ltr drum with integrated fauce
signal word: danger:	In case of accident by inhalation - it can be deadly : remove casualty to fresh air and keep at rest.
	Seek medical advice.



MASTERTEC

SPEZIALARTIKEL FÜR DEN STAHLBETONBAU

storage:

Store in original sealed packages at temperatures between +5 ° C and + 25 ° C. Store out of direct sunlight.

disposal:

Rests of oil dispose at a collecting point for used oil. Don't let in the sewerage. Evacuated canisters may be disposed of at municipal waste landfill sites, taking into account the local waste disposal regulations.

Basis

All dimensions and information in this data sheet reflect the results of the laboratory tests that have been carried out. Deviations from the values determined by us under laboratory conditions are possible due to environmental and operating conditions beyond our control. The data in this data sheet only applies for the product delivered by us. The product data corresponds only to the specifications in Germany. Possible country-specific deviations are not taken into account here.

Indication of law

The technical information reflects our current knowledge of LIDOL 200L MULTI. It is intended only as information for users. As we do not know the envisaged applications and processing conditions, it is the responsibility of the user to carefully check that the product is suitable for the intended purposes. Due to the different components at the installation site and the working conditions in place there, MASTERTEC cannot provide any guarantee whatsoever for the result of the work. Claims arising from any legal relationship can only be recognised in the event of wilful intent or gross negligence, irrespective of the statements made here or advice provided verbally. In this case the user must prove that he has provided MASTERTEC in writing with all the information required to correctly assess the installation situation in good time. Subject to necessary product specifications or further developments. By providing this information MASTERTEC does not intend to infringe third-party rights. The latest data sheet in each case applies. Our corresponding terms and conditions of sale and delivery apply.

The previous data sheets are no longer valid

Printdate 30.12.2020