

data sheet download

LIDOL 30L BIO

concrete release agent

[Show product](#)



article number:	040335
GTIN:	4251689515446
customs tariff number:	34039900
packing unit:	can
sales quantity unit:	30 Liter
weight per:	can = 27.6 kg
material:	renewable primary products
colour:	yellow, clear
consistency:	fluid
	viscosity/20 °C: 14,5 mm ² /s (ASTM D 7042)
density/15 °C:	approx. 890 kg/m ³
pourpoint / DIN ISO 3016:	-12 °C
flash point (accord. Cleveland) / DIN ISO 2592:	>160 °C
GISCODE:	BTM 10
water hazard class :	1 = low hazard to water (accord. AwSV)
application temperature:	0 °C - 60 °C
hydrocarbon:	free
packaging:	30 l canister
certificate:	Due to its high environmental compatibility, LIDOL BIO was awarded the environmental label "Blue Angel" by RAL accord. RAL-UZ 178
storage:	Store in original sealed packages at temperatures between +5 ° C and + 25 ° C. Store out of direct sunlight.
disposal:	Rests of oil dispose at a collecting point for used oil. Don't let in the sewerage. Evacuated canisters may be disposed of at municipal waste landfill sites, taking into account the local waste disposal regulations.

Basis

All dimensions and information in this data sheet reflect the results of the laboratory tests that have been carried out. Deviations from the values determined by us under laboratory conditions are possible due to environmental and operating conditions beyond our control. The data in this data sheet only applies for the product delivered by us. The product data corresponds only to the specifications in Germany. Possible country-specific deviations are not taken into account here.

Indication of law

The technical information reflects our current knowledge of LIDOL 30L BIO . It is intended only as information for users. As we do not know the envisaged applications and processing conditions, it is the responsibility of the user to carefully check that the product is suitable for the intended purposes. Due to the different components at the installation site and the working conditions in place there, MASTERTEC cannot provide any guarantee whatsoever for the result of the work. Claims arising from any legal relationship can only be recognised in the event of wilful intent or gross negligence, irrespective of the statements made here or advice provided verbally. In this case the user must prove that he has provided MASTERTEC in writing with all the information required to correctly assess the installation situation in good time. Subject to necessary product specifications or further developments. By providing this information MASTERTEC does not intend to infringe third-party rights. The latest data sheet in each case applies. Our corresponding terms and conditions of sale and delivery apply.

The previous data sheets are no longer valid

Printdate 30.12.2020