



# MASTERTEC

SPECIAL ARTICLES FOR REINFORCED CONCRETE CONSTRUCTION

## Data sheet

Page 1 of 6

HYDROPHILIC WATERSTOP · JOINT SHEET METAL · INJECTION HOSES | CONSTRUCTION CHEMISTRY · SERVICE DUCTS · LIGHTNING PROTECTION · FORMWORK ACCESSORIES

**MASTERTEC GmbH & Co. KG**  
Gewerbegebiet Unterhaid  
Im Maintal 13  
D-96173 Oberhaid  
Ust.-Id.Nr.: DE 812533130

**Tel.:** +49 (0) 9503 5047-0  
**Mail:** [info@mastertec.eu](mailto:info@mastertec.eu)  
**www.mastertec.eu**  
EORI-Nr.: DE 4774124

Kommanditgesellschaft:  
HRA 9888, Sitz Oberhaid  
Komplementär: BBV Bau-  
Vertriebs-Verwaltungs GmbH,  
HRB 3636 Sitz Oberhaid  
Amtsgericht Bamberg

**Managing directors:**  
Rainer Kropfelder  
Dipl.-Kffr. Gabriele Kropfelder  
Felix Kropfelder, B. Eng.  
Jakob Kropfelder, B. Sc.

**Bank details:**  
Sparkasse Bamberg  
IBAN: DE24 7705 0000 0810 3458 84  
BIC: BYLADEM1 SKB

## STOPPER in 26

for distance tubes ID 26 mm



[Show product](#)



Product video in further languages





article number:	046163
article group:	610 - Stopper + Zubehör
GTIN:	4251689537936
customs tariff number:	39259080
packing unit:	Bucket
sales quantity unit:	250 Stk
weight per:	Bucket = 10 kg
material:	TPE
colour:	grey
density:	ca. 1,17 g/cm <sup>3</sup>
area of application:	for tube with inner diameter 26 mm
hardness:	approx. 70 ± 5 Shore A
test certificates/ approvals:	Pressure watertightness
	Test report MFPA Leipzig
	No. : PB 5.1/17-140-1
	JGS Assessment report
	MPA Braunschweig
	(1200/442/15c) - Pan dt. 28.10.2015
	Fire test
	Test report MFPA Leipzig
	No.: PB 3.2/ 14-354-1

resistances:

e.g.

- Radon
- methan gas
- UV- radiation
- Ozon
- Bitumen

Further resistances are available on request

packaging:	250pcs/ bucket
Substances according to the SVHC list contained or proportional weight $\geq 0.1\%$ :	No
conform to REACH Guideline:	Yes
thermal scope of application:	approx. -35°C up to +70°C
waterpressuretightness:	water column (m) 20 m - 2 bar
firebehavior:	Class "B2", according to DIN 4102 Teil 1  Class "E" according to DIN-EN 13501-1
storage:	In unopened, undamaged original packaging, dry and protected from direct sunlight
disposal:	Observing local authority regulations, it can be disposed of in domestic waste landfills or incinerated

## Basis

All dimensions and information in this data sheet reflect the results of the laboratory tests that have been carried out. Deviations from the values determined by us under laboratory conditions are possible due to environmental and operating conditions beyond our control. The data in this data sheet only applies for the product delivered by us. The product data corresponds only to the specifications in Germany. Possible country-specific deviations are not taken into account here.

## Lifetime

The useful life of buildings is designed for 50 years, and so are the products that are installed. However, this can be shortened by external influences. The expected lifetime of our products depends to a large extent on the installation location (e.g. buried installation, damp environment, offshore, etc.). In addition, there are external influences such as exposure to chemical influences (e.g. acids, aggressive media, aqueous solutions, industrial waste water, oils, etc.) and ambient temperatures / operating temperatures. Ultimately, no generally valid statement can be made about the guaranteed service life of our MASTERTEC products, as this depends on many parameters (use, environmental influences, installation requirements, safety regulations, etc.). To ensure safe operation, we recommend continuous testing of the product, as part of an operating and maintenance manual to be prepared by the customer in accordance with the safety requirements.

## Indication of law

The technical information reflects our current knowledge of the product STOPPER in 26. It is intended only as information for users. As we do not know the envisaged applications and processing conditions, it is the responsibility of the user to carefully check that the product is suitable for the intended purposes. Due to the different components at the installation site and the working conditions in place there, MASTERTEC cannot provide any guarantee whatsoever for the result of the work. Claims arising from any legal relationship can only be recognised in the event of wilful intent or gross negligence, irrespective of the statements made here or advice provided verbally. In this case the user must prove that he has provided MASTERTEC in writing with all the information required to correctly assess the installation situation in good time. Subject to necessary product specifications or further developments.



By providing this information MASTERTEC does not intend to infringe third party rights. The latest data sheet in each case applies. Our corresponding terms and conditions of sale and delivery apply.

**The previous data sheets are no longer valid**

Print date 19.09.2024 , last modified 24.03.2022