

data sheet download

STOPPER Screw Covered Typ 5 - 25 up to 28 mm

Screwed inner seal for pressure water and gas-tight sealing of formwork tie points



[Show product](#)



Productvideo in more languages



article number:	046350
GTIN:	4251689538070
customs tariff number:	39259080
packing unit:	Bucket
sales quantity unit:	100 Stk
weight per:	Bucket = 5.5 kg
material:	screw / nut / pressure plate: stainless steel V2A rubber seal: thermoplastic elastomer claw: polyoxymethylene
colour:	screw: silvery nut: silvery pressure plate: silvery rubber seal: black claw: green
Inner diameter of tie point :	25 to 28 mm
Ø pressure plate :	32 mm
overall length :	65 mm
storage:	Store in undamaged and unopened original packaging in a dry place out of direct sunlight
disposal:	Can be disposed of at municipal waste landfill sites or waste incineration plants, taking into account the local waste disposal regulations

Basis

All dimensions and information in this data sheet reflect the results of the laboratory tests that have been carried out. Deviations from the values determined by us under laboratory conditions are possible due to environmental and operating conditions beyond our control. The data in this data sheet only applies for the product delivered by us. The product data corresponds only to the specifications in Germany. Possible country-specific deviations are not taken into account here.

Indication of law

The technical information reflects our current knowledge of STOPPER Screw Covered Typ 5 - 25 up to 28 mm . It is intended only as information for users. As we do not know the envisaged applications and processing conditions, it is the responsibility of the user to carefully check that the product is suitable for the intended purposes. Due to the different components at the installation site and the working conditions in place there, MASTERTEC cannot provide any guarantee whatsoever for the result of the work. Claims arising from any legal relationship can only be recognised in the event of wilful intent or gross negligence, irrespective of the statements made here or advice provided verbally. In this case the user must prove that he has provided MASTERTEC in writing with all the information required to correctly assess the installation situation in good time. Subject to necessary product specifications or further developments. By providing this information MASTERTEC does not intend to infringe third-party rights. The latest data sheet in each case applies. Our corresponding terms and conditions of sale and delivery apply.

The previous data sheets are no longer valid

Printdate 31.12.2020