


Data sheet

ABS deflection prof(ULP)-reinf. (V)-400-toothed

toothed stopend panels UL 400 reinforced



Show product



Seite 1 von 3

QUELLBÄNDER • FUGENBLECHE • INJEKTIONSSCHLÄUCHE I BAUCHEMIE • DRUCKWASSERDICHTE HAUSEINFÜHRUNGEN • BLITZSCHUTZ • SCHALUNGSZUBEHÖR

MASTERTEC GmbH & Co. KG Gewerbegebiet Unterhaid Im Maintal 13 D-96173 Oberhaid Ust.-Id.Nr.: DE 812533130 Tel.: +49 (0) 9503 5047-0 Fax: +49 (0) 9503 5047-20 info@Mastertec.eu www.Mastertec.eu EORI-Nr.: DE 4774124

Kommanditgesellschaft: HRA 9888, Sitz Oberhaid Komplementär: BBV Bau-Vertriebs-Verwaltungs GmbH, HRB 3636, Sitz Oberhaid Amtsgericht Bamberg Geschäftsführer: Rainer Kropfelder Dipl.-Kffr. Gabriele Kropfelder Felix Kropfelder Jakob Kropfelder, B.Sc. Bankverbindung: Sparkasse Bamberg IBAN: DE24 7705 0000 0810 3458 84 BIC: BYLADEM1 SKB



article group:216 - ABS Profile (ULP, EP, KP, TP) (S+V)GTIN:4251689500442customs tariff number:73269098packing unit:pcsales quantity unit:1 Stkweight per:pc = 4.8 kgmaterial:St 37, galvanizedspecial coating: polymer resin fabric-reinforcedcolour:blackwidth joint sheet metal:160 mmheight perforated plate:400 mmstorage:Store in a dry place out of direct sunlight.disposal:Can be disposed of at municipal waste landfill sites, taking into account the local waste disposal regulations	article number:	070395V
customs tariff number:73269098packing unit:pcsales quantity unit:1 Stkweight per:pc = 4.8 kgmaterial:St 37, galvanizedspecial coating: polymer resin fabric-reinforcedcolour:blackwidth joint sheet metal:160 mmheight perforated plate:400 mmstorage:Store in a dry place out of direct sunlight.disposal:Can be disposed of at municipal waste landfill sites, taking into account the	article group:	216 - ABS Profile (ULP, EP, KP, TP) (S+V)
packing unit:pcsales quantity unit:1 Stkweight per:pc = 4.8 kgmaterial:St 37, galvanizedspecial coating: polymer resin fabric-reinforcedcolour:blackwidth joint sheet metal:160 mmheight perforated plate:400 mmstorage:Store in a dry place out of direct sunlight.disposal:Can be disposed of at municipal waste landfill sites, taking into account the	GTIN:	4251689500442
sales quantity unit: 1 Stk weight per: pc = 4.8 kg material: St 37, galvanized special coating: polymer resin fabric-reinforced colour: black width joint sheet metal: 160 mm height perforated plate: 400 mm storage: Store in a dry place out of direct sunlight. disposal: Can be disposed of at municipal waste landfill sites, taking into account the	customs tariff number:	73269098
weight per: pc = 4.8 kg material: St 37, galvanized special coating: polymer resin fabric-reinforced colour: black width joint sheet metal: 160 mm height perforated plate: 400 mm storage: Store in a dry place out of direct sunlight. disposal: Can be disposed of at municipal waste landfill sites, taking into account the	packing unit:	рс
material: St 37, galvanized special coating: polymer resin fabric-reinforced colour: black width joint sheet metal: 160 mm height perforated plate: 400 mm storage: Store in a dry place out of direct sunlight. disposal: Can be disposed of at municipal waste landfill sites, taking into account the	sales quantity unit:	1 Stk
special coating: polymer resin fabric-reinforced colour: black width joint sheet metal: 160 mm height perforated plate: 400 mm storage: Store in a dry place out of direct sunlight. disposal: Can be disposed of at municipal waste landfill sites, taking into account the	weight per:	pc = 4.8 kg
fabric-reinforced colour: black width joint sheet metal: 160 mm height perforated plate: 400 mm storage: Store in a dry place out of direct sunlight. disposal: Can be disposed of at municipal waste landfill sites, taking into account the	material:	St 37, galvanized
colour:blackwidth joint sheet metal:160 mmheight perforated plate:400 mmstorage:Store in a dry place out of direct sunlight.disposal:Can be disposed of at municipal waste landfill sites, taking into account the		special coating: polymer resin
width joint sheet metal:160 mmheight perforated plate:400 mmstorage:Store in a dry place out of direct sunlight.disposal:Can be disposed of at municipal waste landfill sites, taking into account the		fabric-reinforced
height perforated plate: 400 mm storage: Store in a dry place out of direct sunlight. disposal: Can be disposed of at municipal waste landfill sites, taking into account the	colour:	black
storage: Store in a dry place out of direct sunlight. disposal: Can be disposed of at municipal waste landfill sites, taking into account the	width joint sheet metal:	160 mm
Store in a dry place out of direct sunlight. disposal: Can be disposed of at municipal waste landfill sites, taking into account the	height perforated plate:	400 mm
direct sunlight. disposal: Can be disposed of at municipal waste landfill sites, taking into account the	storage:	
disposal:Can be disposed of at municipal wastelandfill sites, taking into account the		Store in a dry place out of
landfill sites, taking into account the		direct sunlight.
	disposal:	Can be disposed of at municipal waste
local waste disposal regulations		landfill sites, taking into account the
		local waste disposal regulations

Seite 2 von 3

QUELLBÄNDER • FUGENBLECHE • INJEKTIONSSCHLÄUCHE I BAUCHEMIE • DRUCKWASSERDICHTE HAUSEINFÜHRUNGEN • BLITZSCHUTZ • SCHALUNGSZUBEHÖR

MASTERTEC GmbH & Co. KG Gewerbegebiet Unterhaid Im Maintal 13 D-96173 Oberhaid Ust.-Id.Nr.: DE 812533130 Tel.: +49 (0) 9503 5047-0 Fax: +49 (0) 9503 5047-20 info@Mastertec.eu www.Mastertec.eu EORI-Nr.: DE 4774124 Kommanditgesellschaft: HRA 9888, Sitz Oberhaid Komplementär: BBV Bau-Vertriebs-Verwaltungs GmbH, HRB 3636, Sitz Oberhaid Amtsgericht Bamberg

Geschäftsführer: Rainer Kropfelder Dipl.-Kffr. Gabriele Kropfelder Felix Kropfelder Jakob Kropfelder, B.Sc. Bankverbindung: Sparkasse Bamberg IBAN: DE24 7705 0000 0810 3458 84 BIC: BYLADEM1 SKB



Basis

All dimensions and information in this data sheet reflect the results of the laboratory tests that have been carried out. Deviations from the values determined by us under laboratory conditions are possible due to environmental and operating conditions beyond our control. The data in this data sheet only applies for the product delivered by us. The product data corresponds only to the specifications in Germany. Possible country-specific deviations are not taken into account here.

Indication of law

The technical information reflects our current knowledge of ABS deflection prof(ULP)-reinf. (V)-400-toothed. It is intended only as information for users. As we do not know the envisaged applications and processing conditions, it is the responsibility of the user to carefully check that the product is suitable for the intended purposes. Due to the different components at the installation site and the working conditions in place there, MASTERTEC cannot provide any guarantee whatsoever for the result of the work. Claims arising from any legal relationship can only be recognised in the event of wilful intent or gross negligence, irrespective of the statements made here or advice provided verbally. In this case the user must prove that he has provided MASTERTEC in writing with all the information required to correctly assess the installation situation in good time. Subject to necessary product specifications or further developments. By providing this information MASTERTEC does not intend to infringe third party rights. The latest data sheet in each case applies. Our corresponding terms and conditions of sale and delivery apply.

The previous data sheets are no longer valid

Print date 21.05.2024 , last modified 24.03.2022

Seite 3 von 3

QUELLBÄNDER • FUGENBLECHE • INJEKTIONSSCHLÄUCHE I BAUCHEMIE • DRUCKWASSERDICHTE HAUSEINFÜHRUNGEN • BLITZSCHUTZ • SCHALUNGSZUBEHÖR

MASTERTEC GmbH & Co. KG Gewerbegebiet Unterhaid Im Maintal 13 D-96173 Oberhaid Ust.-Id.Nr.: DE 812533130 Tel.: +49 (0) 9503 5047-0 Fax: +49 (0) 9503 5047-20 info@Mastertec.eu www.Mastertec.eu EORI-Nr.: DE 4774124 Kommanditgesellschaft: HRA 9888, Sitz Oberhaid Komplementär: BBV Bau-Vertriebs-Verwaltungs GmbH, HRB 3636, Sitz Oberhaid Amtsgericht Bamberg **Geschäftsführer:** Rainer Kropfelder Dipl.-Kffr. Gabriele Kropfelder Felix Kropfelder Jakob Kropfelder, B.Sc. Bankverbindung: Sparkasse Bamberg IBAN: DE24 7705 0000 0810 3458 84 BIC: BYLADEM1 SKB