

Data sheet

Joint sheet metal roll 120 VB1

one side fully coated









Show product



Product video in further languages





article group: 213 - Dichtblech VB Rollen h = 80, 120, 240 mm GTIN: 4251689511233 customs tariff number: 73269098 packing unit: Roll sales quantity unit: 20 m weight per: Roll = 15 kg material: St 37, galvanized special coating: polymer resin fabric-reinforced colour: black length of joint sheet metal: 20 m height of joint sheet metal: 120 mm thickness of joint sheet approx. 0.6 mm metal: thickness of special approx. 0.15 mm coating: total thickness: approx. 0.75 mm test certificate / approvals: Test report PB 5.1/15-146-2 MFPA Leipzig suitable for zones with frequently varying water levels: corresponds to: Utility class A for the wear classes 1 and 2 in accordance with the WU guideline Substances according to the SVHC list contained or proportional weight ≥0.1%:	article number:	070463
customs tariff number: 73269098 packing unit: Roll sales quantity unit: 20 m weight per: Roll = 15 kg material: St 37, galvanized	article group:	213 - Dichtblech VB Rollen h = 80, 120, 240 mm
packing unit: Roll sales quantity unit: 20 m weight per: Roll = 15 kg material: St 37, galvanized special coating: polymer resin fabric-reinforced colour: black length of joint sheet metal: 20 m height of joint sheet metal: 120 mm thickness of joint sheet approx. 0.6 mm metal: thickness of special approx. 0.15 mm coating: total thickness: approx 0.75 mm test certificate / approvals: Test report PB 5.1/15-146-2 MFPA Leipzig suitable for zones with frequently varying water levels: corresponds to: Utility class A for the wear classes 1 and 2 in accordance with the WU guideline Substances according to the SVHC list contained or proportional weight ≥0.1%:	GTIN:	4251689511233
sales quantity unit: weight per: Roll = 15 kg material: St 37, galvanized special coating: polymer resin fabric-reinforced black length of joint sheet metal: length of joint sheet metal: 120 mm height of joint sheet metal: height of joint sheet approx. 0.6 mm metal: thickness of special coating: total thickness: approx. 0.15 mm coating: total thickness: Test report PB 5.1/15-146-2 MFPA Leipzig suitable for zones with frequently varying water levels: corresponds to: Utility class A for the wear classes 1 and 2 in accordance with the WU guideline Substances according to the SVHC list contained or proportional weight ≥0.1%:	customs tariff number:	73269098
material: St 37, galvanized special coating: polymer resin fabric-reinforced colour: black length of joint sheet metal: 20 m height of joint sheet metal: thickness of joint sheet metal: thickness of special coating: total thickness: approx. 0.75 mm test certificate / approvals: Test report PB 5.1/15-146-2 MFPA Leipzig suitable for zones with frequently varying water levels: corresponds to: Utility class A for the wear classes 1 and 2 in accordance with the WU guideline Substances according to the SVHC list contained or proportional weight ≥0.1%:	packing unit:	Roll
material: St 37, galvanized special coating: polymer resin fabric-reinforced colour: black length of joint sheet metal: length of joint sheet metal: 120 mm thickness of joint sheet metal: thickness of special coating: total thickness: approx. 0.15 mm test certificate / approvals: Test report PB 5.1/15-146-2 MFPA Leipzig suitable for zones with frequently varying water levels: corresponds to: Utility class A for the wear classes 1 and 2 in accordance with the WU guideline Substances according to the SVHC list contained or proportional weight ≥0.1%:	sales quantity unit:	20 m
special coating: polymer resin fabric-reinforced colour: black length of joint sheet metal: 20 m height of joint sheet metal: 120 mm thickness of joint sheet approx. 0.6 mm metal: thickness of special approx. 0.15 mm coating: total thickness: approx. 0.75 mm test certificate / approvals: Test report PB 5.1/15-146-2 MFPA Leipzig suitable for zones with frequently varying water levels: corresponds to: Utility class A for the wear classes 1 and 2 in accordance with the WU guideline Substances according to the SVHC list contained or proportional weight ≥0.1%:	weight per:	Roll = 15 kg
fabric-reinforced colour: black length of joint sheet metal: 20 m height of joint sheet metal: 120 mm thickness of joint sheet approx. 0.6 mm metal: thickness of special approx. 0.15 mm coating: total thickness: approx. 0.75 mm test certificate / approvals: Test report PB 5.1/15-146-2 MFPA Leipzig suitable for zones with frequently varying water levels: corresponds to: Utility class A for the wear classes 1 and 2 in accordance with the WU guideline Substances according to the SVHC list contained or proportional weight ≥0.1%:	material:	St 37, galvanized
colour: black length of joint sheet metal: 20 m height of joint sheet metal: 120 mm thickness of joint sheet approx. 0.6 mm metal: thickness of special approx. 0.15 mm coating: total thickness: approx. 0.75 mm test certificate / approvals: Test report PB 5.1/15-146-2 MFPA Leipzig suitable for zones with yes frequently varying water levels: corresponds to: Utility class A for the wear classes 1 and 2 in accordance with the WU guideline Substances according to the SVHC list contained or proportional weight ≥0.1%:		special coating: polymer resin
length of joint sheet metal: 20 m height of joint sheet metal: 120 mm thickness of joint sheet approx. 0.6 mm metal: thickness of special approx. 0.15 mm coating: total thickness: approx. 0.75 mm test certificate / approvals: Test report PB 5.1/15-146-2 MFPA Leipzig suitable for zones with yes frequently varying water levels: corresponds to: Utility class A for the wear classes 1 and 2 in accordance with the WU guideline Substances according to the SVHC list contained or proportional weight ≥0.1%:		fabric-reinforced
height of joint sheet metal: thickness of joint sheet metal: thickness of special coating: total thickness: approx. 0.75 mm test certificate / approvals: Fest report PB 5.1/15-146-2 MFPA Leipzig suitable for zones with frequently varying water levels: corresponds to: Utility class A for the wear classes 1 and 2 in accordance with the WU guideline Substances according to the SVHC list contained or proportional weight ≥0.1%:	colour:	black
thickness of joint sheet metal: thickness of special approx. 0.15 mm coating: total thickness: approx. 0.75 mm test certificate / approvals: Test report PB 5.1/15-146-2 MFPA Leipzig suitable for zones with frequently varying water levels: corresponds to: Utility class A for the wear classes 1 and 2 in accordance with the WU guideline Substances according to the SVHC list contained or proportional weight ≥0.1%:	length of joint sheet metal:	20 m
thickness of special approx. 0.15 mm coating: total thickness: approx. 0.75 mm test certificate / approvals: Test report PB 5.1/15-146-2 MFPA Leipzig suitable for zones with yes frequently varying water levels: corresponds to: Utility class A for the wear classes 1 and 2 in accordance with the WU guideline Substances according to the SVHC list contained or proportional weight ≥0.1%:	height of joint sheet metal:	120 mm
thickness of special approx. 0.15 mm coating: total thickness: approx. 0.75 mm test certificate / approvals: Test report PB 5.1/15-146-2	thickness of joint sheet	approx. 0.6 mm
total thickness: approx. 0.75 mm test certificate / approvals: Test report PB 5.1/15-146-2	metal:	
total thickness: approx. 0.75 mm test certificate / approvals: Test report PB 5.1/15-146-2 MFPA Leipzig suitable for zones with frequently varying water levels: corresponds to: Utility class A for the wear classes 1 and 2 in accordance with the WU guideline Substances according to the SVHC list contained or proportional weight ≥0.1%:	thickness of special	approx. 0.15 mm
test certificate / approvals: Test report PB 5.1/15-146-2 MFPA Leipzig suitable for zones with frequently varying water levels: corresponds to: Utility class A for the wear classes 1 and 2 in accordance with the WU guideline Substances according to the SVHC list contained or proportional weight ≥0.1%:	coating:	
suitable for zones with frequently varying water levels: corresponds to: Utility class A for the wear classes 1 and 2 in accordance with the WU guideline Substances according to the SVHC list contained or proportional weight ≥0.1%:	total thickness:	approx. 0.75 mm
suitable for zones with frequently varying water levels: corresponds to: Utility class A for the wear classes 1 and 2 in accordance with the WU guideline Substances according to the SVHC list contained or proportional weight ≥0.1%:	test certificate / approvals:	Test report PB 5.1/15-146-2
frequently varying water levels: corresponds to: Utility class A for the wear classes 1 and 2 in accordance with the WU guideline Substances according to the SVHC list contained or proportional weight ≥0.1%:		MFPA Leipzig
levels: corresponds to: Utility class A for the wear classes 1 and 2 in accordance with the WU guideline Substances according to the SVHC list contained or proportional weight ≥0.1%:	suitable for zones with	yes
corresponds to: Utility class A for the wear classes 1 and 2 in accordance with the WU guideline Substances according to the SVHC list contained or proportional weight ≥0.1%:	. , , ,	
2 in accordance with the WU guideline Substances according to No the SVHC list contained or proportional weight ≥0.1%:	levels:	
Substances according to No the SVHC list contained or proportional weight ≥0.1%:	corresponds to:	
the SVHC list contained or proportional weight ≥0.1%:		
proportional weight ≥0.1%:		No
conform to DEACH Voc		
	conform to REACH	Yes
Guideline:	Guideline:	



packaging:	carton (40 x 40 x 20 cm) 1 roll 2 fixing clips 30 mounting brackets
	48 cartons per pallet
thermal scope of	- 20°C to + 90°C
application:	
waterpressuretightness:	Up to max. 6 bar (60 m water column)
storage:	Store in undamaged and unopened
	original packaging in a dry place out of direct sunlight.
disposal:	Can be disposed of at municipal waste landfill sites,
	taking into account the local waste disposal regulations.



Basis

All dimensions and information in this data sheet reflect the results of the laboratory tests that have been carried out. Deviations from the values determined by us under laboratory conditions are possible due to environmental and operating conditions beyond our control. The data in this data sheet only applies for the product delivered by us. The product data corresponds only to the specifications in Germany. Possible country-specific deviations are not taken into account here.

Indication of law

The technical information reflects our current knowledge of Joint sheet metal roll 120 VB1. It is intended only as information for users. As we do not know the envisaged applications and processing conditions, it is the responsibility of the user to carefully check that the product is suitable for the intended purposes. Due to the different components at the installation site and the working conditions in place there, MASTERTEC cannot provide any guarantee whatsoever for the result of the work. Claims arising from any legal relationship can only be recognised in the event of wilful intent or gross negligence, irrespective of the statements made here or advice provided verbally. In this case the user must prove that he has provided MASTERTEC in writing with all the information required to correctly assess the installation situation in good time. Subject to necessary product specifications or further developments. By providing this information MASTERTEC does not intend to infringe third party rights. The latest data sheet in each case applies. Our corresponding terms and conditions of sale and delivery apply.

The previous data sheets are no longer valid

Print date 19.05.2024, last modified 24.03.2022