

Data sheet

MASTER-Connect joint tape B330

for joint tape widths up to 330 mm



Show product



Product video in further languages







article group: 210 - Connect (Blech + Band) GTIN: 4251689513350 customs tariff number: 72123000 packing unit: pc sales quantity unit: 1 Stk weight per: pc = 4 kg material: steel plates: St 37, bright intermediate plates: specialty rubber screws: galvanised colour: grey, black length of the plates: 330 mm width of the plates: 100 mm thickness steelplate / approx. 6 mm / 10 mm thickness steelplate: test certificate / approvals: Investigation report UB 2.2/02-440 MFPA Leipzig pressure water-tightness: 5 bar (50 m water column)	article number:	070620
customs tariff number: 72123000 packing unit: pc sales quantity unit: 1 Stk weight per: pc = 4 kg material: steel plates: St 37, bright	article group:	210 - Connect (Blech + Band)
packing unit: pc sales quantity unit: 1 Stk weight per: pc = 4 kg material: steel plates: St 37, bright intermediate plates: specialty rubber screws: galvanised colour: grey, black length of the plates: 330 mm width of the plates: 100 mm thickness steelplate / approx. 6 mm / 10 mm intermediate plate: test certificate / approvals: Investigation report UB 2.2/02-440 MFPA Leipzig pressure water-tightness: 5 bar (50 m water column)	GTIN:	4251689513350
sales quantity unit: weight per: pc = 4 kg material: steel plates: St 37, bright intermediate plates: specialty rubber screws: galvanised colour: grey, black length of the plates: 100 mm width of the plates: 100 mm thickness steelplate / intermediate plate: test certificate / approvals: Investigation report UB 2.2/02-440 MFPA Leipzig pressure water-tightness: 5 bar (50 m water column) alternative: 2 bar (20 m water column) After deduction of an safety coefficient of 2,5 (Germany) resistances (intermediate plate): Fermentation mash Diluted acids Diluted alkalis	customs tariff number:	72123000
material: material: steel plates: St 37, bright intermediate plates: specialty rubber screws: galvanised colour: grey, black length of the plates: 100 mm width of the plates: 100 mm thickness steelplate / intermediate plate: test certificate / approvals: Investigation report UB 2.2/02-440 MFPA Leipzig pressure water-tightness: 5 bar (50 m water column) alternative: 2 bar (20 m water column) After deduction of an safety coefficient of 2,5 (Germany) resistances (intermediate plate): Fermentation mash Diluted acids Diluted alkalis	packing unit:	рс
material: steel plates: St 37, bright intermediate plates: specialty rubber screws: galvanised colour: grey, black length of the plates: 100 mm width of the plates: 100 mm approx. 6 mm / 10 mm intermediate plate: test certificate / approvals: lnvestigation report UB 2.2/02-440 MFPA Leipzig pressure water-tightness: 5 bar (50 m water column) alternative: 2 bar (20 m water column) After deduction of an safety coefficient of 2,5 (Germany) resistances (intermediate plate): Fermentation mash Diluted acids Diluted alkalis	sales quantity unit:	1 Stk
intermediate plates: specialty rubber screws: galvanised colour: grey, black length of the plates: 330 mm width of the plates: 100 mm thickness steelplate / approx. 6 mm / 10 mm intermediate plate: test certificate / approvals: Investigation report	weight per:	pc = 4 kg
screws: galvanised colour: grey, black length of the plates: 330 mm width of the plates: 100 mm thickness steelplate / approx. 6 mm / 10 mm intermediate plate: test certificate / approvals: Investigation report	material:	steel plates: St 37, bright
colour: grey, black length of the plates: 330 mm width of the plates: 100 mm thickness steelplate / approv. 6 mm / 10 mm intermediate plate: test certificate / approvals: Investigation report		intermediate plates: specialty rubber
length of the plates: 330 mm width of the plates: 100 mm thickness steelplate / approx. 6 mm / 10 mm intermediate plate: test certificate / approvals: Investigation report		screws: galvanised
width of the plates: thickness steelplate / approx. 6 mm / 10 mm intermediate plate: test certificate / approvals: Investigation report UB 2.2/02-440 MFPA Leipzig pressure water-tightness: 5 bar (50 m water column) alternative: 2 bar (20 m water column) After deduction of an safety coefficient of 2,5 (Germany) resistances (intermediate plate): Fermentation mash Diluted acids Diluted alkalis	colour:	grey, black
thickness steelplate / approx. 6 mm / 10 mm intermediate plate: test certificate / approvals: Investigation report	length of the plates:	330 mm
intermediate plate: test certificate / approvals: Investigation report	width of the plates:	100 mm
test certificate / approvals: Investigation report UB 2.2/02-440 MFPA Leipzig pressure water-tightness: 5 bar (50 m water column) alternative: 2 bar (20 m water column) After deduction of an safety coefficient of 2,5 (Germany) resistances (intermediate plate): Fermentation mash Diluted acids Diluted alkalis	thickness steelplate /	approx. 6 mm / 10 mm
UB 2.2/02-440 MFPA Leipzig pressure water-tightness: 5 bar (50 m water column) alternative: 2 bar (20 m water column) After deduction of an safety coefficient of 2,5 (Germany) resistances (intermediate plate): Fermentation mash Diluted acids Diluted alkalis	intermediate plate:	
pressure water-tightness: 5 bar (50 m water column) alternative: 2 bar (20 m water column) After deduction of an safety coefficient of 2,5 (Germany) resistances (intermediate plate): Fermentation mash Diluted acids Diluted alkalis	test certificate / approvals:	Investigation report
pressure water-tightness: 5 bar (50 m water column) alternative: 2 bar (20 m water column) After deduction of an safety coefficient of 2,5 (Germany) resistances (intermediate plate): Fermentation mash Diluted acids Diluted alkalis		UB 2.2/02-440
alternative: 2 bar (20 m water column) After deduction of an safety coefficient of 2,5 (Germany) resistances (intermediate plate): Fermentation mash Diluted acids Diluted alkalis		MFPA Leipzig
2 bar (20 m water column) After deduction of an safety coefficient of 2,5 (Germany) resistances (intermediate Liquid manure and slurry plate): Fermentation mash Diluted acids Diluted alkalis	pressure water-tightness:	5 bar (50 m water column)
2 bar (20 m water column) After deduction of an safety coefficient of 2,5 (Germany) resistances (intermediate Liquid manure and slurry plate): Fermentation mash Diluted acids Diluted alkalis		
After deduction of an safety coefficient of 2,5 (Germany) resistances (intermediate Liquid manure and slurry plate): Fermentation mash Diluted acids Diluted alkalis		alternative:
After deduction of an safety coefficient of 2,5 (Germany) resistances (intermediate Liquid manure and slurry plate): Fermentation mash Diluted acids Diluted alkalis		
coefficient of 2,5 (Germany) resistances (intermediate Liquid manure and slurry plate): Fermentation mash Diluted acids Diluted alkalis		` '
resistances (intermediate Liquid manure and slurry plate): Fermentation mash Diluted acids Diluted alkalis		After deduction of an safety
plate): Fermentation mash Diluted acids Diluted alkalis		coefficient of 2,5 (Germany)
Diluted acids Diluted alkalis	resistances (intermediate	Liquid manure and slurry
Diluted alkalis	plate):	Fermentation mash
		Diluted acids
packing unit: 1 piece per carton		Diluted alkalis
	packing unit:	1 piece per carton



scope of delivery: 2 pcs. Steel plates, bright

2 pcs. Specialty rubber plates,

6/8 pcs. NBR washers

3/4 pcs. M 10 screws, galvanised 3/4 pcs. M 10 nuts, galvanised

The product is delivered pre-assembled in a box

	·
Substances according to	No
the SVHC list contained or	
proportional weight ≥0.1%:	
conform to REACH	Yes
Guideline:	
storage:	Store in undamaged and unopened original packaging in a
	dry place out of direct sunlight.
disposal:	Can be disposed of at municipal waste landfill sites,
	taking into account the local waste disposal regulations.



Basis

All dimensions and information in this data sheet reflect the results of the laboratory tests that have been carried out. Deviations from the values determined by us under laboratory conditions are possible due to environmental and operating conditions beyond our control. The data in this data sheet only applies for the product delivered by us. The product data corresponds only to the specifications in Germany. Possible country-specific deviations are not taken into account here.

Indication of law

The technical information reflects our current knowledge ofMASTER-Connect joint tape B330. It is intended only as information for users. As we do not know the envisaged applications and processing conditions, it is the responsibility of the user to carefully check that the product is suitable for the intended purposes. Due to the different components at the installation site and the working conditions in place there, MASTERTEC cannot provide any guarantee whatsoever for the result of the work. Claims arising from any legal relationship can only be recognised in the event of wilful intent or gross negligence, irrespective of the statements made here or advice provided verbally. In this case the user must prove that he has provided MASTERTEC in writing with all the information required to correctly assess the installation situation in good time. Subject to necessary product specifications or further developments. By providing this information MASTERTEC does not intend to infringe third party rights. The latest data sheet in each case applies. Our corresponding terms and conditions of sale and delivery apply.

The previous data sheets are no longer valid

Print date 08.05.2024, last modified 24.03.2022