

## Data sheet

# Expansion joint tape, external, DA 32

tape width 320 mm roll length 25 m

**Show product** 



Seite 1 von 4



article group: 211 - PVC Fugenband und Dichtungsrohr GTIN: 4251689513589  customs tariff number: 39162000  packing unit: Roll sales quantity unit: 25 m  weight per: Roll = 68 kg  material: PVC-P  NB (not compatible with bitumen)  colour: black roll length: 25 m  tape width (a): 320 mm  expansion part width (b): 105 mm  expansion part thickness 4 mm  (c): height of anchors (f): 25 mm  number of anchors: 6 pieces shore-hardness A: 72 ± 5°, acc. to DIN 53505 elongation at break: min. ≥ 275%, acc. to DIN EN ISO 527-2  tensile strength: min. ≥ 10 N/mm², DIN EN ISO 527-2  Substances according to the SVHC list contained or proportional weight ≥0.1%: conform to REACH Yes Guideline: storage: Store in undamaged and unopened original packaging in a dry place out of direct sunlight.	article number:	080700
customs tariff number: 39162000  packing unit: Roll  sales quantity unit: 25 m  weight per: Roll = 68 kg  material: PVC-P  NB (not compatible with bitumen)  colour: black  roll length: 25 m  tape width (a): 320 mm   expansion part width (b): 105 mm  expansion part thickness (c):  height of anchors (f): 25 mm  number of anchors: 6 pieces  shore-hardness A: 72 ± 5°, acc. to DIN 53505  elongation at break: min. ≥ 275%, acc. to  DIN EN ISO 527-2  tensile strength: min. ≥ 10 N/mm²,  DIN EN ISO 527-2  Substances according to the SVHC list contained or proportional weight ≥0.1%:  conform to REACH Yes  Guideline:  storage: Store in undamaged and unopened	article group:	211 - PVC Fugenband und Dichtungsrohr
packing unit:  sales quantity unit:  25 m  weight per:  Roll = 68 kg  material:  PVC-P  NB (not compatible with bitumen)  colour:  black  roll length:  25 m  tape width (a):  expansion part width (b):  expansion part thickness (c):  height of anchors (f):  25 mm   105 mm  expansion part thickness (c):  height of anchors (f):  25 mm  number of anchors:  6 pieces  shore-hardness A:  72 ± 5°, acc. to DIN 53505  elongation at break:  min. ≥ 275%, acc. to DIN EN ISO 527-2  tensile strength:  min. ≥ 10 N/mm², DIN EN ISO 527-2  Substances according to the SVHC list contained or proportional weight ≥0.1%:  conform to REACH Guideline:  storage:  Store in undamaged and unopened	GTIN:	4251689513589
sales quantity unit:  weight per: Roll = 68 kg  material: PVC-P NB (not compatible with bitumen)  colour: black roll length: 25 m  tape width (a):  expansion part width (b): expansion part thickness (c): height of anchors (f):  number of anchors: 6 pieces shore-hardness A: 72 ± 5°, acc. to DIN 53505  elongation at break: min. ≥ 275%, acc. to DIN EN ISO 527-2  tensile strength: min. ≥ 10 N/mm², DIN EN ISO 527-2  Substances according to the SVHC list contained or proportional weight ≥0.1%: conform to REACH Guideline: storage: Store in undamaged and unopened	customs tariff number:	39162000
weight per: Roll = 68 kg   material: PVC-P   NB (not compatible with bitumen)   colour: black   roll length: 25 m   tape width (a): 320 mm   expansion part width (b): 105 mm   expansion part thickness 4 mm   (c): height of anchors (f):   number of anchors: 6 pieces   shore-hardness A: 72 ± 5°, acc. to DIN 53505   elongation at break: min. ≥ 275%, acc. to   DIN EN ISO 527-2   tensile strength: min. ≥ 10 N/mm²,   DIN EN ISO 527-2   Substances according to the SVHC list contained or proportional weight ≥0.1%: No   conform to REACH Guideline: Yes   storage: Store in undamaged and unopened	packing unit:	Roll
material:  PVC-P  NB (not compatible with bitumen)  colour: black  roll length: 25 m  tape width (a):  expansion part width (b): expansion part thickness (c): height of anchors (f):  number of anchors: shore-hardness A: place 275 m  number of anchors: black  min. ≥ 275%, acc. to DIN 53505  elongation at break: min. ≥ 275%, acc. to DIN EN ISO 527-2  tensile strength: min. ≥ 10 N/mm², DIN EN ISO 527-2  Substances according to the SVHC list contained or proportional weight ≥0.1%: conform to REACH Guideline: storage: Store in undamaged and unopened	sales quantity unit:	25 m
NB (not compatible with bitumen)  colour: black  roll length: 25 m  tape width (a): 320 mm   expansion part width (b): 105 mm  expansion part thickness 4 mm  (c):  height of anchors (f): 25 mm   number of anchors: 6 pieces  shore-hardness A: 72 ± 5°, acc. to DIN 53505  elongation at break: min. ≥ 275%, acc. to  DIN EN ISO 527-2  tensile strength: min. ≥ 10 N/mm²,  DIN EN ISO 527-2  Substances according to the SVHC list contained or proportional weight ≥0.1%:  conform to REACH Yes  Guideline:  storage: Store in undamaged and unopened	weight per:	Roll = 68 kg
colour: black roll length: 25 m  tape width (a): 320 mm  expansion part width (b): 105 mm  expansion part thickness 4 mm (c): height of anchors (f): 25 mm  number of anchors: 6 pieces shore-hardness A: 72 ± 5°, acc. to DIN 53505 elongation at break: min. ≥ 275%, acc. to DIN EN ISO 527-2  tensile strength: min. ≥ 10 N/mm², DIN EN ISO 527-2  Substances according to No the SVHC list contained or proportional weight ≥0.1%: conform to REACH Yes Guideline: storage: Store in undamaged and unopened	material:	PVC-P
roll length:  tape width (a):  25 m  expansion part width (b):  expansion part thickness (c):  height of anchors (f):  number of anchors: 6 pieces  shore-hardness A: 72 ± 5°, acc. to DIN 53505  elongation at break:  min. ≥ 275%, acc. to DIN EN ISO 527-2  tensile strength:  min. ≥ 10 N/mm², DIN EN ISO 527-2  Substances according to the SVHC list contained or proportional weight ≥0.1%:  conform to REACH Guideline:  storage:  Store in undamaged and unopened		NB (not compatible with bitumen)
tape width (a):    2320 mm	colour:	black
expansion part width (b):  expansion part thickness (c):  height of anchors (f):  number of anchors:  shore-hardness A:  elongation at break:  DIN EN ISO 527-2  tensile strength:  min. ≥ 10 N/mm², DIN EN ISO 527-2  Substances according to the SVHC list contained or proportional weight ≥0.1%:  conform to REACH Guideline:  storage:  Store in undamaged and unopened	roll length:	25 m
expansion part thickness (c):  height of anchors (f):  number of anchors: 6 pieces shore-hardness A: 72 ± 5°, acc. to DIN 53505 elongation at break: min. ≥ 275%, acc. to DIN EN ISO 527-2  tensile strength: min. ≥ 10 N/mm², DIN EN ISO 527-2  Substances according to the SVHC list contained or proportional weight ≥0.1%: conform to REACH Guideline: storage: Store in undamaged and unopened	tape width (a):	320 mm
expansion part thickness (c):  height of anchors (f):  number of anchors: 6 pieces shore-hardness A: 72 ± 5°, acc. to DIN 53505 elongation at break: min. ≥ 275%, acc. to DIN EN ISO 527-2  tensile strength: min. ≥ 10 N/mm², DIN EN ISO 527-2  Substances according to the SVHC list contained or proportional weight ≥0.1%: conform to REACH Guideline: storage: Store in undamaged and unopened		
(c): height of anchors (f):  25 mm  number of anchors: 6 pieces shore-hardness A: 72 ± 5°, acc. to DIN 53505 elongation at break: min. ≥ 275%, acc. to DIN EN ISO 527-2  tensile strength: min. ≥ 10 N/mm², DIN EN ISO 527-2  Substances according to the SVHC list contained or proportional weight ≥0.1%: conform to REACH Guideline: storage: Store in undamaged and unopened	expansion part width (b):	105 mm
height of anchors (f):    Discrete	expansion part thickness	4 mm
number of anchors: 6 pieces  shore-hardness A: 72 ± 5°, acc. to DIN 53505  elongation at break: min. ≥ 275%, acc. to	(c):	
shore-hardness A: $72 \pm 5^{\circ}$ , acc. to DIN 53505  elongation at break: $min. \ge 275\%$ , acc. to DIN EN ISO 527-2  tensile strength: $min. \ge 10 \text{ N/mm}^2$ , DIN EN ISO 527-2  Substances according to No the SVHC list contained or proportional weight $\ge 0.1\%$ : conform to REACH Yes Guideline: storage: Store in undamaged and unopened	height of anchors (f):	25 mm
shore-hardness A: $72 \pm 5^{\circ}$ , acc. to DIN 53505  elongation at break: min. $\geq 275\%$ , acc. to DIN EN ISO 527-2  tensile strength: min. $\geq 10 \text{ N/mm}^2$ , DIN EN ISO 527-2  Substances according to No the SVHC list contained or proportional weight $\geq 0.1\%$ : conform to REACH Yes Guideline: storage: Store in undamaged and unopened		
elongation at break:  min. ≥ 275%, acc. to  DIN EN ISO 527-2  tensile strength:  min. ≥ 10 N/mm²,  DIN EN ISO 527-2  Substances according to the SVHC list contained or proportional weight ≥0.1%:  conform to REACH  Guideline:  storage:  Store in undamaged and unopened	number of anchors:	6 pieces
$DIN \ EN \ ISO \ 527-2$ $tensile \ strength: \qquad min. \ge 10 \ N/mm^2, \\ DIN \ EN \ ISO \ 527-2$ $Substances \ according \ to \\ the \ SVHC \ list \ contained \ or \\ proportional \ weight \ge 0.1\%: \\ conform \ to \ REACH \qquad Yes \\ Guideline: \\ storage: \qquad Store \ in \ undamaged \ and \ unopened$	shore-hardness A:	72 ± 5°, acc. to DIN 53505
tensile strength: $min. \ge 10 \text{ N/mm}^2$ , $DIN \text{ EN ISO } 527-2$ Substances according to No the SVHC list contained or proportional weight $\ge 0.1\%$ : conform to REACH Yes Guideline: storage: Store in undamaged and unopened	elongation at break:	min. ≥ 275%, acc. to
DIN EN ISO 527-2  Substances according to No the SVHC list contained or proportional weight ≥0.1%:  conform to REACH Yes Guideline: Storage: Store in undamaged and unopened		DIN EN ISO 527-2
Substances according to the SVHC list contained or proportional weight ≥0.1%:  conform to REACH  Guideline:  storage:  Store in undamaged and unopened	tensile strength:	min. ≥ 10 N/mm²,
the SVHC list contained or proportional weight ≥0.1%:  conform to REACH Yes  Guideline:  storage: Store in undamaged and unopened		DIN EN ISO 527-2
proportional weight ≥0.1%:  conform to REACH Yes  Guideline:  storage: Store in undamaged and unopened	Substances according to	No
conform to REACH  Guideline:  storage:  Store in undamaged and unopened	the SVHC list contained or	
Guideline: storage: Store in undamaged and unopened	proportional weight ≥0.1%:	
storage: Store in undamaged and unopened	conform to REACH	Yes
	Guideline:	
original packaging in a dry place out of direct sunlight.	storage:	Store in undamaged and unopened
		original packaging in a dry place out of direct sunlight.

Seite 2 von 4



disposal: Can be disposed of at municipal waste landfill sites,

taking into account the

local waste disposal regulations.

Seite 3 von 4



#### **Basis**

All dimensions and information in this data sheet reflect the results of the laboratory tests that have been carried out. Deviations from the values determined by us under laboratory conditions are possible due to environmental and operating conditions beyond our control. The data in this data sheet only applies for the product delivered by us. The product data corresponds only to the specifications in Germany. Possible country-specific deviations are not taken into account here.

#### **Indication of law**

The technical information reflects our current knowledge of Expansion joint tape, external, DA 32. It is intended only as information for users. As we do not know the envisaged applications and processing conditions, it is the responsibility of the user to carefully check that the product is suitable for the intended purposes. Due to the different components at the installation site and the working conditions in place there, MASTERTEC cannot provide any guarantee whatsoever for the result of the work. Claims arising from any legal relationship can only be recognised in the event of wilful intent or gross negligence, irrespective of the statements made here or advice provided verbally. In this case the user must prove that he has provided MASTERTEC in writing with all the information required to correctly assess the installation situation in good time. Subject to necessary product specifications or further developments. By providing this information MASTERTEC does not intend to infringe third party rights. The latest data sheet in each case applies. Our corresponding terms and conditions of sale and delivery apply.

### The previous data sheets are no longer valid

Print date 19.04.2024, last modified 24.03.2022