

Data sheet

High-pressure lining pipe DURO Plus Ø 250/200 DW3

Double-wall (DW) type





Show product



Seite 1 von 3

QUELLBÄNDER • FUGENBLECHE • INJEKTIONSSCHLÄUCHE I BAUCHEMIE • DRUCKWASSERDICHTE HAUSEINFÜHRUNGEN • BLITZSCHUTZ • SCHALUNGSZUBEHÖR

MASTERTEC GmbH & Co. KG Gewerbegebiet Unterhaid Im Maintal 13 D-96173 Oberhaid Ust.-Id.Nr.: DE 812533130 Tel.: +49 (0) 9503 5047-0 Fax: +49 (0) 9503 5047-20 info@Mastertec.eu www.Mastertec.eu EORI-Nr.: DE 4774124 Kommanditgesellschaft: HRA 9888, Sitz Oberhaid Komplementär: BBV Bau-Vertriebs-Verwaltungs GmbH, HRB 3636, Sitz Oberhaid Amtsgericht Bamberg

Geschäftsführer: Rainer Kropfelder Dipl.-Kffr. Gabriele Kropfelder Felix Kropfelder Jakob Kropfelder, B.Sc. Bankverbindung: Sparkasse Bamberg IBAN: DE24 7705 0000 0810 3458 84 BIC: BYLADEM1 SKB



| article group:403 - Duro + DW3GTIN:4251689532221customs tariff number:39172310packing unit:pcsales quantity unit:1 Stkweight per:pc = 2.3 kgmaterial:pipe: PVCsealing: TPEcolour:pipe: blacksealing: greenthermal scope of- 30° C bis 60°Capplication:7 barstorage:Store dry and protected from direct sunlightdisposal:Can be disposed of at municipal waste landfill sites, taking into account the | article number: | 090670 |
|--|-------------------------|--|
| customs tariff number:39172310packing unit:pcsales quantity unit:1 Stkweight per:pc = 2.3 kgmaterial:pipe: PVCsealing: TPEcolour:pipe: black sealing: greenthermal scope of application:- 30° C bis 60°C application:waterpressuretightness:7 barstorage:Store dry and protected from direct sunlight disposal: | article group: | 403 - Duro + DW3 |
| packing unit:pcsales quantity unit:1 Stkweight per:pc = 2.3 kgmaterial:pipe: PVCsealing: TPEcolour:pipe: blacksealing: greenthermal scope of- 30° C bis 60°Capplication:waterpressuretightness:7 barstorage:Store dry and protected from direct sunlightdisposal:Can be disposed of at municipal waste | GTIN: | 4251689532221 |
| sales quantity unit:1 Stkweight per:pc = 2.3 kgmaterial:pipe: PVCsealing: TPEcolour:pipe: black sealing: greenthermal scope of application:- 30° C bis 60°Cwaterpressuretightness:7 barstorage:Store dry and protected from direct sunlightdisposal:Can be disposed of at municipal waste | customs tariff number: | 39172310 |
| weight per:pc = 2.3 kgmaterial:pipe: PVCsealing: TPEcolour:pipe: black sealing: greenthermal scope of application:- 30° C bis 60°C application:waterpressuretightness:7 barstorage:Store dry and protected from direct sunlight disposal:disposal:Can be disposed of at municipal waste | packing unit: | рс |
| material:pipe: PVCsealing: TPEcolour:pipe: black sealing: greenthermal scope of application:- 30° C bis 60°Cwaterpressuretightness:7 barstorage:Store dry and protected from direct sunlightdisposal:Can be disposed of at municipal waste | sales quantity unit: | 1 Stk |
| sealing: TPE colour: pipe: black sealing: green thermal scope of application: - 30° C bis 60°C waterpressuretightness: 7 bar storage: Store dry and protected from direct sunlight disposal: Can be disposed of at municipal waste | weight per: | pc = 2.3 kg |
| colour:pipe: black sealing: greenthermal scope of application:- 30° C bis 60°Cwaterpressuretightness:7 barstorage:Store dry and protected from direct sunlightdisposal:Can be disposed of at municipal waste | material: | pipe: PVC |
| sealing: greenthermal scope of application:waterpressuretightness:7 barstorage:Store dry and protected from direct sunlightdisposal:Can be disposed of at municipal waste | | sealing: TPE |
| thermal scope of application:- 30° C bis 60°Cwaterpressuretightness:7 barstorage:Store dry and protected from direct sunlightdisposal:Can be disposed of at municipal waste | colour: | pipe: black |
| application:waterpressuretightness:7 barstorage:Store dry and protected from direct sunlightdisposal:Can be disposed of at municipal waste | | sealing: green |
| waterpressuretightness:7 barstorage:Store dry and protected from direct sunlightdisposal:Can be disposed of at municipal waste | thermal scope of | - 30° C bis 60°C |
| storage:Store dry and protected from direct sunlightdisposal:Can be disposed of at municipal waste | application: | |
| disposal: Can be disposed of at municipal waste | waterpressuretightness: | 7 bar |
| | storage: | Store dry and protected from direct sunlight |
| landfill sites, taking into account the | disposal: | Can be disposed of at municipal waste |
| | | landfill sites, taking into account the |
| local waste disposal regulations. | | local waste disposal regulations. |

Seite 2 von 3

QUELLBÄNDER • FUGENBLECHE • INJEKTIONSSCHLÄUCHE I BAUCHEMIE • DRUCKWASSERDICHTE HAUSEINFÜHRUNGEN • BLITZSCHUTZ • SCHALUNGSZUBEHÖR

MASTERTEC GmbH & Co. KG Gewerbegebiet Unterhaid Im Maintal 13 D-96173 Oberhaid Ust.-Id.Nr.: DE 812533130 Tel.: +49 (0) 9503 5047-0 Fax: +49 (0) 9503 5047-20 info@Mastertec.eu www.Mastertec.eu EORI-Nr.: DE 4774124 Kommanditgesellschaft: HRA 9888, Sitz Oberhaid Komplementär: BBV Bau-Vertriebs-Verwaltungs GmbH, HRB 3636, Sitz Oberhaid Amtsgericht Bamberg

Geschäftsführer: Rainer Kropfelder Dipl.-Kffr. Gabriele Kropfelder Felix Kropfelder Jakob Kropfelder, B.Sc. Bankverbindung: Sparkasse Bamberg IBAN: DE24 7705 0000 0810 3458 84 BIC: BYLADEM1 SKB



Basis

All dimensions and information in this data sheet reflect the results of the laboratory tests that have been carried out. Deviations from the values determined by us under laboratory conditions are possible due to environmental and operating conditions beyond our control. The data in this data sheet only applies for the product delivered by us. The product data corresponds only to the specifications in Germany. Possible country-specific deviations are not taken into account here.

Indication of law

The technical information reflects our current knowledge of High-pressure lining pipe DURO Plus Ø 250/200 DW3. It is intended only as information for users. As we do not know the envisaged applications and processing conditions, it is the responsibility of the user to carefully check that the product is suitable for the intended purposes. Due to the different components at the installation site and the working conditions in place there, MASTERTEC cannot provide any guarantee whatsoever for the result of the work. Claims arising from any legal relationship can only be recognised in the event of wilful intent or gross negligence, irrespective of the statements made here or advice provided verbally. In this case the user must prove that he has provided MASTERTEC in writing with all the information required to correctly assess the installation situation in good time. Subject to necessary product specifications or further developments. By providing this information MASTERTEC does not intend to infringe third party rights. The latest data sheet in each case applies. Our corresponding terms and conditions of sale and delivery apply.

The previous data sheets are no longer valid

Print date 21.05.2024 , last modified 24.03.2022

Seite 3 von 3

QUELLBÄNDER • FUGENBLECHE • INJEKTIONSSCHLÄUCHE I BAUCHEMIE • DRUCKWASSERDICHTE HAUSEINFÜHRUNGEN • BLITZSCHUTZ • SCHALUNGSZUBEHÖR

MASTERTEC GmbH & Co. KG Gewerbegebiet Unterhaid Im Maintal 13 D-96173 Oberhaid Ust.-Id.Nr.: DE 812533130 Tel.: +49 (0) 9503 5047-0 Fax: +49 (0) 9503 5047-20 info@Mastertec.eu www.Mastertec.eu EORI-Nr.: DE 4774124 Kommanditgesellschaft: HRA 9888, Sitz Oberhaid Komplementär: BBV Bau-Vertriebs-Verwaltungs GmbH, HRB 3636, Sitz Oberhaid Amtsgericht Bamberg **Geschäftsführer:** Rainer Kropfelder Dipl.-Kffr. Gabriele Kropfelder Felix Kropfelder Jakob Kropfelder, B.Sc. Bankverbindung: Sparkasse Bamberg IBAN: DE24 7705 0000 0810 3458 84 BIC: BYLADEM1 SKB