

Data sheet

Cross connector flat/round-galvanised

for round conductors \emptyset 8 + 10 mm and earthing strap up to 30 mm width Galvanised steel, 2-part, flat/round heavy duty version, M8 screws



Show product





Seite 1 von 3



article group: 512 - Kreuzverbinder GTIN: 4251689533648 customs tariff number: 73269060 packing unit: pc sales quantity unit: 1 Stk weight per: pc = 0.2 kg material: FeZn colour: silvery material thickness: 3,1 mm screw: 4 x M8 x 25 mm norm: DIN EN 62561-1 Lightning current carrying capability class: packing: carton / 50 pcs Clamping range: Round wire: Ø 8-10 mm Earthing strap: up to 30 mm Dimensions: 55 x 55 mm	article number:	100115
customs tariff number: 73269060 packing unit: pc sales quantity unit: 1 Stk weight per: pc = 0.2 kg material: FeZn colour: silvery material thickness: 3,1 mm screw: 4 x M8 x 25 mm norm: DIN EN 62561-1 Lightning current carrying rapability class: packing: carton / 50 pcs Clamping range: Round wire: Ø 8-10 mm Earthing strap: up to 30 mm	article group:	512 - Kreuzverbinder
packing unit: sales quantity unit: 1 Stk weight per: pc = 0.2 kg material: FeZn colour: silvery material thickness: 3,1 mm screw: 4 x M8 x 25 mm norm: DIN EN 62561-1 Lightning current carrying capability class: packing: carton / 50 pcs Clamping range: Round wire: Ø 8-10 mm Earthing strap: up to 30 mm	GTIN:	4251689533648
sales quantity unit: 1 Stk weight per: pc = 0.2 kg material: FeZn colour: silvery material thickness: 3,1 mm screw: 4 x M8 x 25 mm norm: DIN EN 62561-1 Lightning current carrying capability class: packing: Carton / 50 pcs Clamping range: Round wire: Ø 8-10 mm Earthing strap: up to 30 mm	customs tariff number:	73269060
weight per: pc = 0.2 kg material: FeZn colour: silvery material thickness: 3,1 mm screw: 4 x M8 x 25 mm norm: DIN EN 62561-1 Lightning current carrying capability class: packing: carton / 50 pcs Clamping range: Round wire: Ø 8-10 mm Earthing strap: up to 30 mm	packing unit:	рс
material: colour: silvery material thickness: 3,1 mm screw: 4 x M8 x 25 mm norm: DIN EN 62561-1 Lightning current carrying capability class: packing: carton / 50 pcs Clamping range: Round wire: Ø 8-10 mm Earthing strap: up to 30 mm	sales quantity unit:	1 Stk
colour: silvery material thickness: 3,1 mm screw: 4 x M8 x 25 mm norm: DIN EN 62561-1 Lightning current carrying H (100kA) capability class: packing: carton / 50 pcs Clamping range: Round wire: Ø 8-10 mm Earthing strap: up to 30 mm	weight per:	pc = 0.2 kg
material thickness: 3,1 mm screw: 4 x M8 x 25 mm norm: DIN EN 62561-1 Lightning current carrying H (100kA) capability class: packing: carton / 50 pcs Clamping range: Round wire: Ø 8-10 mm Earthing strap: up to 30 mm	material:	FeZn
screw: 4 x M8 x 25 mm norm: DIN EN 62561-1 Lightning current carrying H (100kA) capability class: packing: carton / 50 pcs Clamping range: Round wire: Ø 8-10 mm Earthing strap: up to 30 mm	colour:	silvery
norm: Lightning current carrying H (100kA) capability class: packing: Clamping range: Round wire: Ø 8-10 mm Earthing strap: up to 30 mm	material thickness:	3,1 mm
Lightning current carrying H (100kA) capability class: packing: carton / 50 pcs Clamping range: Round wire: Ø 8-10 mm Earthing strap: up to 30 mm	screw:	4 x M8 x 25 mm
capability class: packing: carton / 50 pcs Clamping range: Round wire: Ø 8-10 mm Earthing strap: up to 30 mm	norm:	DIN EN 62561-1
packing: carton / 50 pcs Clamping range: Round wire: Ø 8-10 mm Earthing strap : up to 30 mm	Lightning current carrying	H (100kA)
Clamping range: Round wire: Ø 8-10 mm Earthing strap : up to 30 mm	capability class:	
Earthing strap : up to 30 mm	packing:	carton / 50 pcs
	Clamping range:	Round wire: Ø 8-10 mm
Dimensions: 55 x 55 mm		Earthing strap : up to 30 mm
	Dimensions:	55 x 55 mm



Basis

All dimensions and information in this data sheet reflect the results of the laboratory tests that have been carried out. Deviations from the values determined by us under laboratory conditions are possible due to environmental and operating conditions beyond our control. The data in this data sheet only applies for the product delivered by us. The product data corresponds only to the specifications in Germany. Possible country-specific deviations are not taken into account here.

Indication of law

The technical information reflects our current knowledge of Cross connector flat/round-galvanised. It is intended only as information for users. As we do not know the envisaged applications and processing conditions, it is the responsibility of the user to carefully check that the product is suitable for the intended purposes. Due to the different components at the installation site and the working conditions in place there, MASTERTEC cannot provide any guarantee whatsoever for the result of the work. Claims arising from any legal relationship can only be recognised in the event of wilful intent or gross negligence, irrespective of the statements made here or advice provided verbally. In this case the user must prove that he has provided MASTERTEC in writing with all the information required to correctly assess the installation situation in good time. Subject to necessary product specifications or further developments. By providing this information MASTERTEC does not intend to infringe third party rights. The latest data sheet in each case applies. Our corresponding terms and conditions of sale and delivery apply.

The previous data sheets are no longer valid

Print date 13.05.2024, last modified 24.03.2022