

Data sheet

MASTER-SEAL modular seal Ø 125 mm - galvanised

for core drill hole or lining pipe DN 125 mm medium pipe
outer Ø 45 up to 52 mm



[Show product](#)



Product video in further
languages



article number:	110634
article group:	445 - Master Seal A2+vz+Einzelglieder
GTIN:	4251689530074
customs tariff number:	40169300
packing unit:	chain
sales quantity unit:	1 chain
weight per:	chain = 1 kg
material:	pressure plates: polyamide strengthened
	sealing element: EPDM caoutchouc
	screws-nuts: galvanised
colour:	pressure plates: red
	sealing element: black
	screws-nuts: silvery
Screws:	M10
Number of screws:	4
Wrench size:	17 mm
Max. torque:	35 Nm (dimensionally stable medium pipes)
Installation depth:	90 mm
waterpressuretightness:	3 bar
Medium pipe:	45 to 52 mm

Basis

All dimensions and information in this data sheet reflect the results of the laboratory tests that have been carried out. Deviations from the values determined by us under laboratory conditions are possible due to environmental and operating conditions beyond our control. The data in this data sheet only applies for the product delivered by us. The product data corresponds only to the specifications in Germany. Possible country-specific deviations are not taken into account here.

Indication of law

The technical information reflects our current knowledge of MASTER-SEAL modular seal Ø 125 mm - galvanised. It is intended only as information for users. As we do not know the envisaged applications and processing conditions, it is the responsibility of the user to carefully check that the product is suitable for the intended purposes. Due to the different components at the installation site and the working conditions in place there, MASTERTEC cannot provide any guarantee whatsoever for the result of the work. Claims arising from any legal relationship can only be recognised in the event of wilful intent or gross negligence, irrespective of the statements made here or advice provided verbally. In this case the user must prove that he has provided MASTERTEC in writing with all the information required to correctly assess the installation situation in good time. Subject to necessary product specifications or further developments. By providing this information MASTERTEC does not intend to infringe third party rights. The latest data sheet in each case applies. Our corresponding terms and conditions of sale and delivery apply.

The previous data sheets are no longer valid

Print date 19.05.2024