

Data sheet

MASTER-SEAL modular seal Ø 500 mm - galvanised

for core drill hole or lining pipe DN 500 mm medium pipe outer \emptyset 409 up to 419 mm



Show product





Product video in further languages



Seite 1 von 3

QUELLBÄNDER • FUGENBLECHE • INJEKTIONSSCHLÄUCHE I BAUCHEMIE • DRUCKWASSERDICHTE HAUSEINFÜHRUNGEN • BLITZSCHUTZ • SCHALUNGSZUBEHÖR

MASTERTEC GmbH & Co. KG Gewerbegebiet Unterhaid Im Maintal 13 D-96173 Oberhaid Ust.-Id.Nr.: DE 812533130 Tel.: +49 (0) 9503 5047-0 Fax: +49 (0) 9503 5047-20 info@Mastertec.eu www.Mastertec.eu EORI-Nr.: DE 4774124 Kommanditgesellschaft: HRA 9888, Sitz Oberhaid Komplementär: BBV Bau-Vertriebs-Verwaltungs GmbH, HRB 3636, Sitz Oberhaid Amtsgericht Bamberg

Geschäftsführer: Rainer Kropfelder Dipl.-Kffr. Gabriele Kropfelder Felix Kropfelder Jakob Kropfelder, B.Sc. Bankverbindung: Sparkasse Bamberg IBAN: DE24 7705 0000 0810 3458 84 BIC: BYLADEM1 SKB



article group:445 - Master Seal A2+vz+EinzelgliederGTIN:4251689530593customs tariff number:40169300packing unit:chainsales quantity unit:1 chainweight per:chain = 5.4 kgmaterial:pressure plates: polyamide strengthenedsealing element: EPDM caoutchoucscrews-nuts: galvanisedcolour:pressure plates: redsealing element: blackscrews-nuts: silveryScrews:M10Number of screws:21Wrench size:17 mmMax. torque:35 Nm (dimensionally stable medium pipes)Installation depth:90 mmwutappraceuvatiabtnege:2 her	article number:	110805
customs tariff number:40169300packing unit:chainsales quantity unit:1 chainweight per:chain = 5.4 kgmaterial:pressure plates: polyamide strengthenedsealing element: EPDM caoutchoucscrews-nuts: galvanisedcolour:pressure plates: redsealing element: blackscrews-nuts: silveryScrews:M10Number of screws:21Wrench size:17 mmMax. torque:35 Nm (dimensionally stable medium pipes)Installation depth:90 mm	article group:	445 - Master Seal A2+vz+Einzelglieder
packing unit:chainsales quantity unit:1 chainweight per:chain = 5.4 kgmaterial:pressure plates: polyamide strengthenedsealing element: EPDM caoutchoucscrews-nuts: galvanisedcolour:pressure plates: redsealing element: blackscrews-nuts: silveryScrews:M10Number of screws:21Wrench size:17 mmMax. torque:35 Nm (dimensionally stable medium pipes)Installation depth:90 mm	GTIN:	4251689530593
sales quantity unit: 1 chain weight per: chain = 5.4 kg material: pressure plates: polyamide strengthened sealing element: EPDM caoutchouc screws-nuts: galvanised colour: pressure plates: red sealing element: black screws-nuts: silvery Screws: M10 Number of screws: 21 Wrench size: 17 mm Max. torque: 35 Nm (dimensionally stable medium pipes) Installation depth: 90 mm	customs tariff number:	40169300
weight per:chain = 5.4 kgmaterial:pressure plates: polyamide strengthenedsealing element: EPDM caoutchoucscrews-nuts: galvanisedcolour:pressure plates: redsealing element: blackscrews-nuts: silveryScrews:M10Number of screws:21Wrench size:17 mmMax. torque:35 Nm (dimensionally stable medium pipes)Installation depth:90 mm	packing unit:	chain
material:pressure plates: polyamide strengthenedsealing element: EPDM caoutchoucscrews-nuts: galvanisedcolour:pressure plates: redsealing element: blackscrews-nuts: silveryScrews:M10Number of screws:21Wrench size:17 mmMax. torque:35 Nm (dimensionally stable medium pipes)Installation depth:90 mm	sales quantity unit:	1 chain
sealing element: EPDM caoutchouc screws-nuts: galvanised colour: pressure plates: red sealing element: black screws-nuts: silvery Screws: M10 Number of screws: 21 Wrench size: 17 mm Max. torque: 35 Nm (dimensionally stable medium pipes) Installation depth: 90 mm	weight per:	chain = 5.4 kg
screws-nuts: galvanisedcolour:pressure plates: red sealing element: black screws-nuts: silveryScrews:M10Number of screws:21Wrench size:17 mmMax. torque:35 Nm (dimensionally stable medium pipes)Installation depth:90 mm	material:	pressure plates: polyamide strengthened
colour:pressure plates: red sealing element: black screws-nuts: silveryScrews:M10Number of screws:21Wrench size:17 mmMax. torque:35 Nm (dimensionally stable medium pipes)Installation depth:90 mm		sealing element: EPDM caoutchouc
Screws:M10Number of screws:21Wrench size:17 mmMax. torque:35 Nm (dimensionally stable medium pipes)Installation depth:90 mm		screws-nuts: galvanised
screws-nuts: silveryScrews:M10Number of screws:21Wrench size:17 mmMax. torque:35 Nm (dimensionally stable medium pipes)Installation depth:90 mm	colour:	pressure plates: red
Screws:M10Number of screws:21Wrench size:17 mmMax. torque:35 Nm (dimensionally stable medium pipes)Installation depth:90 mm		sealing element: black
Number of screws:21Wrench size:17 mmMax. torque:35 Nm (dimensionally stable medium pipes)Installation depth:90 mm		screws-nuts: silvery
Wrench size:17 mmMax. torque:35 Nm (dimensionally stable medium pipes)Installation depth:90 mm	Screws:	M10
Max. torque:35 Nm (dimensionally stable medium pipes)Installation depth:90 mm	Number of screws:	21
Installation depth: 90 mm	Wrench size:	17 mm
	Max. torque:	35 Nm (dimensionally stable medium pipes)
waterpropuratightpape: 2 bar	Installation depth:	90 mm
waterpressurenginness. 5 bai	waterpressuretightness:	3 bar
Medium pipe: 409 to 419 mm	Medium pipe:	409 to 419 mm

Seite 2 von 3

QUELLBÄNDER • FUGENBLECHE • INJEKTIONSSCHLÄUCHE I BAUCHEMIE • DRUCKWASSERDICHTE HAUSEINFÜHRUNGEN • BLITZSCHUTZ • SCHALUNGSZUBEHÖR

MASTERTEC GmbH & Co. KG Gewerbegebiet Unterhaid Im Maintal 13 D-96173 Oberhaid Ust.-Id.Nr.: DE 812533130 Tel.: +49 (0) 9503 5047-0 Fax: +49 (0) 9503 5047-20 info@Mastertec.eu www.Mastertec.eu EORI-Nr.: DE 4774124 Kommanditgesellschaft: HRA 9888, Sitz Oberhaid Komplementär: BBV Bau-Vertriebs-Verwaltungs GmbH, HRB 3636, Sitz Oberhaid Amtsgericht Bamberg

Geschäftsführer: Rainer Kropfelder Dipl.-Kffr. Gabriele Kropfelder Felix Kropfelder Jakob Kropfelder, B.Sc. Bankverbindung: Sparkasse Bamberg IBAN: DE24 7705 0000 0810 3458 84 BIC: BYLADEM1 SKB



Basis

All dimensions and information in this data sheet reflect the results of the laboratory tests that have been carried out. Deviations from the values determined by us under laboratory conditions are possible due to environmental and operating conditions beyond our control. The data in this data sheet only applies for the product delivered by us. The product data corresponds only to the specifications in Germany. Possible country-specific deviations are not taken into account here.

Indication of law

The technical information reflects our current knowledge of MASTER-SEAL modular seal Ø 500 mm - galvanised. It is intended only as information for users. As we do not know the envisaged applications and processing conditions, it is the responsibility of the user to carefully check that the product is suitable for the intended purposes. Due to the different components at the installation site and the working conditions in place there, MASTERTEC cannot provide any guarantee whatsoever for the result of the work. Claims arising from any legal relationship can only be recognised in the event of wilful intent or gross negligence, irrespective of the statements made here or advice provided verbally. In this case the user must prove that he has provided MASTERTEC in writing with all the information required to correctly assess the installation situation in good time. Subject to necessary product specifications or further developments. By providing this information MASTERTEC does not intend to infringe third party rights. The latest data sheet in each case applies. Our corresponding terms and conditions of sale and delivery apply.

The previous data sheets are no longer valid

Print date 19.05.2024 , last modified 24.03.2022

Seite 3 von 3

QUELLBÄNDER • FUGENBLECHE • INJEKTIONSSCHLÄUCHE I BAUCHEMIE • DRUCKWASSERDICHTE HAUSEINFÜHRUNGEN • BLITZSCHUTZ • SCHALUNGSZUBEHÖR

MASTERTEC GmbH & Co. KG Gewerbegebiet Unterhaid Im Maintal 13 D-96173 Oberhaid Ust.-Id.Nr.: DE 812533130 Tel.: +49 (0) 9503 5047-0 Fax: +49 (0) 9503 5047-20 info@Mastertec.eu www.Mastertec.eu EORI-Nr.: DE 4774124 Kommanditgesellschaft: HRA 9888, Sitz Oberhaid Komplementär: BBV Bau-Vertriebs-Verwaltungs GmbH, HRB 3636, Sitz Oberhaid Amtsgericht Bamberg **Geschäftsführer:** Rainer Kropfelder Dipl.-Kffr. Gabriele Kropfelder Felix Kropfelder Jakob Kropfelder, B.Sc. Bankverbindung: Sparkasse Bamberg IBAN: DE24 7705 0000 0810 3458 84 BIC: BYLADEM1 SKB