

# Data sheet

# MASTER-SEAL modular seal Ø 600 mm - galvanised

for core drill hole or lining pipe DN 600 mm medium pipe outer  $\emptyset$  440 up to 458 mm



# Show product





Product video in further languages



## Seite 1 von 3

QUELLBÄNDER • FUGENBLECHE • INJEKTIONSSCHLÄUCHE I BAUCHEMIE • DRUCKWASSERDICHTE HAUSEINFÜHRUNGEN • BLITZSCHUTZ • SCHALUNGSZUBEHÖR

MASTERTEC GmbH & Co. KG Gewerbegebiet Unterhaid Im Maintal 13 D-96173 Oberhaid Ust.-Id.Nr.: DE 812533130 Tel.: +49 (0) 9503 5047-0 Fax: +49 (0) 9503 5047-20 info@Mastertec.eu www.Mastertec.eu EORI-Nr.: DE 4774124 Kommanditgesellschaft: HRA 9888, Sitz Oberhaid Komplementär: BBV Bau-Vertriebs-Verwaltungs GmbH, HRB 3636, Sitz Oberhaid Amtsgericht Bamberg

Geschäftsführer: Rainer Kropfelder Dipl.-Kffr. Gabriele Kropfelder Felix Kropfelder Jakob Kropfelder, B.Sc. Bankverbindung: Sparkasse Bamberg IBAN: DE24 7705 0000 0810 3458 84 BIC: BYLADEM1 SKB



article group:445 - Master Seal A2+vz+EinzelgliederGTIN:4251689530654customs tariff number:40169300packing unit:chainsales quantity unit:1 chainweight per:chain = 15.8 kgmaterial:pressure plates: polyamide strengthenedsealing element: EPDM caoutchoucscrews-nuts: galvanisedcolour:pressure plates: redsealing element: blackscrews-nuts: silveryScrews:M16Number of screws:16Wrench size:24 mmMax. torque:85 Nm (dimensionally stable medium pipes)	article number:	110835
customs tariff number:40169300packing unit:chainsales quantity unit:1 chainweight per:chain = 15.8 kgmaterial:pressure plates: polyamide strengthenedsealing element: EPDM caoutchoucscrews-nuts: galvanisedcolour:pressure plates: redsealing element: blackscrews-nuts: silveryScrews:M16Number of screws:16Wrench size:24 mm	article group:	445 - Master Seal A2+vz+Einzelglieder
packing unit:chainsales quantity unit:1 chainweight per:chain = 15.8 kgmaterial:pressure plates: polyamide strengthenedsealing element: EPDM caoutchoucscrews-nuts: galvanisedcolour:pressure plates: redsealing element: blackscrews-nuts: silveryScrews:M16Number of screws:16Wrench size:24 mm	GTIN:	4251689530654
sales quantity unit:   1 chain     weight per:   chain = 15.8 kg     material:   pressure plates: polyamide strengthened     sealing element: EPDM caoutchouc     screws-nuts: galvanised     colour:   pressure plates: red     sealing element: black     screws-nuts: silvery     Screws:   M16     Number of screws:   16     Wrench size:   24 mm	customs tariff number:	40169300
weight per:   chain = 15.8 kg     material:   pressure plates: polyamide strengthened     sealing element: EPDM caoutchouc     screws-nuts: galvanised     colour:   pressure plates: red     sealing element: black     screws-nuts: silvery     Screws:   M16     Number of screws:   16     Wrench size:   24 mm	packing unit:	chain
material:pressure plates: polyamide strengthenedsealing element: EPDM caoutchoucscrews-nuts: galvanisedcolour:pressure plates: redsealing element: blackscrews-nuts: silveryScrews:M16Number of screws:16Wrench size:24 mm	sales quantity unit:	1 chain
sealing element: EPDM caoutchouc     screws-nuts: galvanised     colour:   pressure plates: red     sealing element: black     screws-nuts: silvery     Screws:   M16     Number of screws:   16     Wrench size:   24 mm	weight per:	chain = 15.8 kg
screws-nuts: galvanised     colour:   pressure plates: red     sealing element: black     screws-nuts: silvery     Screws:   M16     Number of screws:   16     Wrench size:   24 mm	material:	pressure plates: polyamide strengthened
colour:   pressure plates: red     sealing element: black     screws-nuts: silvery     Screws:   M16     Number of screws:   16     Wrench size:   24 mm		sealing element: EPDM caoutchouc
Screws: M16   Number of screws: 16   Wrench size: 24 mm		screws-nuts: galvanised
screws-nuts: silveryScrews:M16Number of screws:16Wrench size:24 mm	colour:	pressure plates: red
Screws:M16Number of screws:16Wrench size:24 mm		sealing element: black
Number of screws:16Wrench size:24 mm		screws-nuts: silvery
Wrench size: 24 mm	Screws:	M16
	Number of screws:	16
Max. torque: 85 Nm (dimensionally stable medium pipes)	Wrench size:	24 mm
	Max. torque:	85 Nm (dimensionally stable medium pipes)
Installation depth: 110 mm	Installation depth:	110 mm
waterpressuretightness: 3 bar	waterpressuretightness:	3 bar
Medium pipe: 440 to 458 mm	Medium pipe:	440 to 458 mm

#### Seite 2 von 3

QUELLBÄNDER • FUGENBLECHE • INJEKTIONSSCHLÄUCHE I BAUCHEMIE • DRUCKWASSERDICHTE HAUSEINFÜHRUNGEN • BLITZSCHUTZ • SCHALUNGSZUBEHÖR

MASTERTEC GmbH & Co. KG Gewerbegebiet Unterhaid Im Maintal 13 D-96173 Oberhaid Ust.-Id.Nr.: DE 812533130 Tel.: +49 (0) 9503 5047-0 Fax: +49 (0) 9503 5047-20 info@Mastertec.eu www.Mastertec.eu EORI-Nr.: DE 4774124 Kommanditgesellschaft: HRA 9888, Sitz Oberhaid Komplementär: BBV Bau-Vertriebs-Verwaltungs GmbH, HRB 3636, Sitz Oberhaid Amtsgericht Bamberg

Geschäftsführer: Rainer Kropfelder Dipl.-Kffr. Gabriele Kropfelder Felix Kropfelder Jakob Kropfelder, B.Sc. Bankverbindung: Sparkasse Bamberg IBAN: DE24 7705 0000 0810 3458 84 BIC: BYLADEM1 SKB



# Basis

All dimensions and information in this data sheet reflect the results of the laboratory tests that have been carried out. Deviations from the values determined by us under laboratory conditions are possible due to environmental and operating conditions beyond our control. The data in this data sheet only applies for the product delivered by us. The product data corresponds only to the specifications in Germany. Possible country-specific deviations are not taken into account here.

# **Indication of law**

The technical information reflects our current knowledge of MASTER-SEAL modular seal Ø 600 mm - galvanised. It is intended only as information for users. As we do not know the envisaged applications and processing conditions, it is the responsibility of the user to carefully check that the product is suitable for the intended purposes. Due to the different components at the installation site and the working conditions in place there, MASTERTEC cannot provide any guarantee whatsoever for the result of the work. Claims arising from any legal relationship can only be recognised in the event of wilful intent or gross negligence, irrespective of the statements made here or advice provided verbally. In this case the user must prove that he has provided MASTERTEC in writing with all the information required to correctly assess the installation situation in good time. Subject to necessary product specifications or further developments. By providing this information MASTERTEC does not intend to infringe third party rights. The latest data sheet in each case applies. Our corresponding terms and conditions of sale and delivery apply.

## The previous data sheets are no longer valid

Print date 19.05.2024 , last modified 24.03.2022

Seite 3 von 3

QUELLBÄNDER • FUGENBLECHE • INJEKTIONSSCHLÄUCHE I BAUCHEMIE • DRUCKWASSERDICHTE HAUSEINFÜHRUNGEN • BLITZSCHUTZ • SCHALUNGSZUBEHÖR

MASTERTEC GmbH & Co. KG Gewerbegebiet Unterhaid Im Maintal 13 D-96173 Oberhaid Ust.-Id.Nr.: DE 812533130 Tel.: +49 (0) 9503 5047-0 Fax: +49 (0) 9503 5047-20 info@Mastertec.eu www.Mastertec.eu EORI-Nr.: DE 4774124 Kommanditgesellschaft: HRA 9888, Sitz Oberhaid Komplementär: BBV Bau-Vertriebs-Verwaltungs GmbH, HRB 3636, Sitz Oberhaid Amtsgericht Bamberg **Geschäftsführer:** Rainer Kropfelder Dipl.-Kffr. Gabriele Kropfelder Felix Kropfelder Jakob Kropfelder, B.Sc. Bankverbindung: Sparkasse Bamberg IBAN: DE24 7705 0000 0810 3458 84 BIC: BYLADEM1 SKB