

Data sheet

MASTER-RING Multi Multiple 150mm



4 way onion ring technology; 2 x 4 - 32 mm; 2 x 22-54 mm



Show product



Seite 1 von 4



article group: 444 - RRD Multi -mehrfach- GTIN: 4251689528736 customs tariff number: 84842000 packing unit: pc sales quantity unit: 1 Stk weight per: pc = 1.8 kg material: rubber: EPDM sealing width: 40 mm pressure plates, screws, nuts: V2 A colour: rubber: black pressure plates: silvery Medium pipes in mm: After removing plug and rings (4 - 32 mm): 1: 4 - 7 mm 2: 8 - 12 mm 3: 13 - 17 mm 4: 18 - 22 mm 5: 23 - 27 mm 6: 28 - 32 mm After removing plug and rings (22 - 54 mm): 1: 22 - 26 mm 2: 27 - 31 mm 3: 32 - 36 mm 4: 37 - 41 mm 5: 42 - 46 mm 6: 47 - 51 mm 7: 52 - 56 mm max. torque: 5 Nm at form stable media pipes thermal scope of application: waterpressuretightness: up to 1,5 bar (with occupancy and without)	article number:	120278
customs tariff number: packing unit: pc sales quantity unit: 1 Stk weight per: pc = 1.8 kg material: rubber: EPDM sealing width: 40 mm pressure plates, screws, nuts: V2 A colour: rubber: black pressure plates: silvery Medium pipes in mm: After removing plug and rings (4 - 32 mm): 1: 4 - 7 mm 2: 8 - 12 mm 3: 13 - 17 mm 4: 18 - 22 mm 5: 23 - 27 mm 6: 28 - 32 mm After removing plug and rings (22 - 54 mm): 1: 22 - 26 mm 2: 27 - 31 mm 3: 32 - 36 mm 4: 37 - 41 mm 5: 42 - 46 mm 6: 47 - 51 mm 7: 52 - 56 mm max. torque: 5 Nm at form stable media pipes thermal scope of application:	article group:	444 - RRD Multi -mehrfach-
packing unit: sales quantity unit: 1 Stk weight per: pc = 1.8 kg material: rubber: EPDM sealing width: 40 mm pressure plates, screws, nuts: V2 A colour: rubber: black pressure plates: silvery Medium pipes in mm: After removing plug and rings (4 - 32 mm): 1: 4 - 7 mm 2: 8 - 12 mm 3: 13 - 17 mm 4: 18 - 22 mm 5: 23 - 27 mm 6: 28 - 32 mm After removing plug and rings (22 - 54 mm): 1: 22 - 26 mm 2: 27 - 31 mm 3: 32 - 36 mm 4: 37 - 41 mm 5: 42 - 46 mm 6: 47 - 51 mm 7: 52 - 56 mm max. torque: 5 Nm at form stable media pipes thermal scope of application:	GTIN:	4251689528736
sales quantity unit: 1 Stk weight per: pc = 1.8 kg material: rubber: EPDM sealing width: 40 mm pressure plates, screws, nuts: V2 A colour: rubber: black pressure plates: silvery Medium pipes in mm: After removing plug and rings (4 - 32 mm): 1: 4 - 7 mm 2: 8 - 12 mm 3: 13 - 17 mm 4: 18 - 22 mm 5: 23 - 27 mm 6: 28 - 32 mm After removing plug and rings (22 - 54 mm): 1: 22 - 26 mm 2: 27 - 31 mm 3: 32 - 36 mm 4: 37 - 41 mm 5: 42 - 46 mm 6: 47 - 51 mm 7: 52 - 56 mm max. torque: 5 Nm at form stable media pipes thermal scope of application: approx30° C up to +120° C	customs tariff number:	84842000
weight per: pc = 1.8 kg material: rubber: EPDM sealing width: 40 mm pressure plates, screws, nuts: V2 A colour: rubber: black pressure plates: silvery Medium pipes in mm: After removing plug and rings (4 - 32 mm): 1: 4 - 7 mm 2: 8 - 12 mm 3: 13 - 17 mm 4: 18 - 22 mm 5: 23 - 27 mm 6: 28 - 32 mm After removing plug and rings (22 - 54 mm): 1: 22 - 26 mm 2: 27 - 31 mm 3: 32 - 36 mm 4: 37 - 41 mm 5: 42 - 46 mm 6: 47 - 51 mm 7: 52 - 56 mm max. torque: 5 Nm at form stable media pipes thermal scope of application: approx30° C up to +120° C	packing unit:	рс
material: rubber: EPDM sealing width: 40 mm pressure plates, screws, nuts: V2 A colour: rubber: black pressure plates: silvery Medium pipes in mm: After removing plug and rings (4 - 32 mm): 1: 4 - 7 mm 2: 8 - 12 mm 3: 13 - 17 mm 4: 18 - 22 mm 5: 23 - 27 mm 6: 28 - 32 mm After removing plug and rings (22 - 54 mm): 1: 22 - 26 mm 2: 27 - 31 mm 3: 32 - 36 mm 4: 37 - 41 mm 5: 42 - 46 mm 6: 47 - 51 mm 7: 52 - 56 mm max. torque: 5 Nm at form stable media pipes thermal scope of approx30° C up to +120° C application:	sales quantity unit:	1 Stk
sealing width: 40 mm pressure plates, screws, nuts: V2 A colour: rubber: black pressure plates: silvery Medium pipes in mm: After removing plug and rings (4 - 32 mm): 1: 4 - 7 mm 2: 8 - 12 mm 3: 13 - 17 mm 4: 18 - 22 mm 5: 23 - 27 mm 6: 28 - 32 mm After removing plug and rings (22 - 54 mm): 1: 22 - 26 mm 2: 27 - 31 mm 3: 32 - 36 mm 4: 37 - 41 mm 5: 42 - 46 mm 6: 47 - 51 mm 7: 52 - 56 mm max. torque: 5 Nm at form stable media pipes thermal scope of application:	weight per:	pc = 1.8 kg
pressure plates, screws, nuts: V2 A colour: rubber: black pressure plates: silvery Medium pipes in mm: After removing plug and rings (4 - 32 mm): 1: 4 - 7 mm 2: 8 - 12 mm 3: 13 - 17 mm 4: 18 - 22 mm 5: 23 - 27 mm 6: 28 - 32 mm After removing plug and rings (22 - 54 mm): 1: 22 - 26 mm 2: 27 - 31 mm 3: 32 - 36 mm 4: 37 - 41 mm 5: 42 - 46 mm 6: 47 - 51 mm 7: 52 - 56 mm max. torque: 5 Nm at form stable media pipes thermal scope of application:	material:	rubber: EPDM
rubber: black pressure plates: silvery Medium pipes in mm: After removing plug and rings (4 - 32 mm): 1: 4 - 7 mm 2: 8 - 12 mm 3: 13 - 17 mm 4: 18 - 22 mm 5: 23 - 27 mm 6: 28 - 32 mm After removing plug and rings (22 - 54 mm): 1: 22 - 26 mm 2: 27 - 31 mm 3: 32 - 36 mm 4: 37 - 41 mm 5: 42 - 46 mm 6: 47 - 51 mm 7: 52 - 56 mm max. torque: 5 Nm at form stable media pipes thermal scope of application:		sealing width: 40 mm
Desiration		
Medium pipes in mm: After removing plug and rings (4 - 32 mm): 1: 4 - 7 mm 2: 8 - 12 mm 3: 13 - 17 mm 4: 18 - 22 mm 5: 23 - 27 mm 6: 28 - 32 mm After removing plug and rings (22 - 54 mm): 1: 22 - 26 mm 2: 27 - 31 mm 3: 32 - 36 mm 4: 37 - 41 mm 5: 42 - 46 mm 6: 47 - 51 mm 7: 52 - 56 mm max. torque: 5 Nm at form stable media pipes thermal scope of application: approx30° C up to +120° C	colour:	rubber: black
1: 4 - 7 mm 2: 8 - 12 mm 3: 13 - 17 mm 4: 18 - 22 mm 5: 23 - 27 mm 6: 28 - 32 mm After removing plug and rings (22 - 54 mm): 1: 22 - 26 mm 2: 27 - 31 mm 3: 32 - 36 mm 4: 37 - 41 mm 5: 42 - 46 mm 6: 47 - 51 mm 7: 52 - 56 mm max. torque: 5 Nm at form stable media pipes thermal scope of application:		pressure plates: silvery
2: 8 - 12 mm 3: 13 - 17 mm 4: 18 - 22 mm 5: 23 - 27 mm 6: 28 - 32 mm After removing plug and rings (22 - 54 mm): 1: 22 - 26 mm 2: 27 - 31 mm 3: 32 - 36 mm 4: 37 - 41 mm 5: 42 - 46 mm 6: 47 - 51 mm 7: 52 - 56 mm max. torque: 5 Nm at form stable media pipes thermal scope of application:	Medium pipes in mm:	After removing plug and rings (4 - 32 mm):
3: 13 - 17 mm 4: 18 - 22 mm 5: 23 - 27 mm 6: 28 - 32 mm After removing plug and rings (22 - 54 mm): 1: 22 - 26 mm 2: 27 - 31 mm 3: 32 - 36 mm 4: 37 - 41 mm 5: 42 - 46 mm 6: 47 - 51 mm 7: 52 - 56 mm max. torque: 5 Nm at form stable media pipes thermal scope of application:		1: 4 - 7 mm
4: 18 - 22 mm 5: 23 - 27 mm 6: 28 - 32 mm After removing plug and rings (22 - 54 mm): 1: 22 - 26 mm 2: 27 - 31 mm 3: 32 - 36 mm 4: 37 - 41 mm 5: 42 - 46 mm 6: 47 - 51 mm 7: 52 - 56 mm max. torque: 5 Nm at form stable media pipes thermal scope of application:		2: 8 - 12 mm
5: 23 - 27 mm 6: 28 - 32 mm After removing plug and rings (22 - 54 mm): 1: 22 - 26 mm 2: 27 - 31 mm 3: 32 - 36 mm 4: 37 - 41 mm 5: 42 - 46 mm 6: 47 - 51 mm 7: 52 - 56 mm max. torque: 5 Nm at form stable media pipes thermal scope of application:		3: 13 - 17 mm
6: 28 - 32 mm After removing plug and rings (22 - 54 mm): 1: 22 - 26 mm 2: 27 - 31 mm 3: 32 - 36 mm 4: 37 - 41 mm 5: 42 - 46 mm 6: 47 - 51 mm 7: 52 - 56 mm max. torque: 5 Nm at form stable media pipes thermal scope of application:		4: 18 - 22 mm
After removing plug and rings (22 - 54 mm): 1: 22 - 26 mm 2: 27 - 31 mm 3: 32 - 36 mm 4: 37 - 41 mm 5: 42 - 46 mm 6: 47 - 51 mm 7: 52 - 56 mm max. torque: 5 Nm at form stable media pipes thermal scope of application:		5: 23 - 27 mm
1: 22 - 26 mm 2: 27 - 31 mm 3: 32 - 36 mm 4: 37 - 41 mm 5: 42 - 46 mm 6: 47 - 51 mm 7: 52 - 56 mm max. torque: 5 Nm at form stable media pipes thermal scope of approx30° C up to +120° C application:		6: 28 - 32 mm
2: 27 - 31 mm 3: 32 - 36 mm 4: 37 - 41 mm 5: 42 - 46 mm 6: 47 - 51 mm 7: 52 - 56 mm max. torque: 5 Nm at form stable media pipes thermal scope of approx30° C up to +120° C application:		After removing plug and rings (22 - 54 mm):
3: 32 - 36 mm 4: 37 - 41 mm 5: 42 - 46 mm 6: 47 - 51 mm 7: 52 - 56 mm max. torque: 5 Nm at form stable media pipes thermal scope of approx30° C up to +120° C application:		1: 22 - 26 mm
4: 37 - 41 mm 5: 42 - 46 mm 6: 47 - 51 mm 7: 52 - 56 mm max. torque: 5 Nm at form stable media pipes thermal scope of approx30° C up to +120° C application:		2: 27 - 31 mm
5: 42 - 46 mm 6: 47 - 51 mm 7: 52 - 56 mm max. torque: 5 Nm at form stable media pipes thermal scope of approx30° C up to +120° C application:		3: 32 - 36 mm
6: 47 - 51 mm 7: 52 - 56 mm max. torque: 5 Nm at form stable media pipes thermal scope of approx30° C up to +120° C application:		4: 37 - 41 mm
7: 52 - 56 mm max. torque: 5 Nm at form stable media pipes thermal scope of approx30° C up to +120° C application:		5: 42 - 46 mm
max. torque: 5 Nm at form stable media pipes thermal scope of approx30° C up to +120° C application:		6: 47 - 51 mm
thermal scope of approx30° C up to +120° C application:		7: 52 - 56 mm
application:	max. torque:	5 Nm at form stable media pipes
		approx30° C up to +120° C
waterpressuretightness: up to 1,5 bar (with occupancy and without)	application:	
	waterpressuretightness:	up to 1,5 bar (with occupancy and without)

Seite 2 von 4



storage:	Store in a dry place out of direct sunlight
disposal:	Can be disposed of at municipal waste landfill sites,
	taking into account the local waste disposal regulations.



Basis

All dimensions and information in this data sheet reflect the results of the laboratory tests that have been carried out. Deviations from the values determined by us under laboratory conditions are possible due to environmental and operating conditions beyond our control. The data in this data sheet only applies for the product delivered by us. The product data corresponds only to the specifications in Germany. Possible country-specific deviations are not taken into account here.

Indication of law

The technical information reflects our current knowledge ofMASTER-RING Multi Multiple 150mm. It is intended only as information for users. As we do not know the envisaged applications and processing conditions, it is the responsibility of the user to carefully check that the product is suitable for the intended purposes. Due to the different components at the installation site and the working conditions in place there, MASTERTEC cannot provide any guarantee whatsoever for the result of the work. Claims arising from any legal relationship can only be recognised in the event of wilful intent or gross negligence, irrespective of the statements made here or advice provided verbally. In this case the user must prove that he has provided MASTERTEC in writing with all the information required to correctly assess the installation situation in good time. Subject to necessary product specifications or further developments. By providing this information MASTERTEC does not intend to infringe third party rights. The latest data sheet in each case applies. Our corresponding terms and conditions of sale and delivery apply.

The previous data sheets are no longer valid

Print date 18.05.2024, last modified 25.09.2023